



MINOR SUBDIVISION APPLICATION (a total of three or fewer lots) City of Rochester, New Hampshire

	[office use only. Check#	Amount	\$	Date paid]	
Date: _7-9-18					
Property information	(If so, we encourage yo	u to submit an a	pplication a	s soon as possible.)	
Tax map #: _246; Lo	t #('s): <u>27</u> ; ;	Zoning district:	R1		
Property address/location:					
Name of project (if applicab					
Size of site: 9.63 Ac acres	; overlay zoning distric	t(s)? Wetlands			
Property owner					
Name (include name of ind	ividual): David & De	stiny Groen			
Mailing address: 138 Che					
Telephone #:603-817-935					
Applicant/developer (if					
Name (include name of indi	ividual): _Same				
Mailing address:					
Telephone #:		Email:			
Engineer/surveyor	Venneth 7 I				
Name (include name of indi	vidual): <u>Berry Surve</u>	Berry, PE, I eying & Eng	LLS ineering		
Mailing address: 335 Seco					
Telephone #: 603-332-	-2863	Fax #: 603	-335-462	3	
Email address: crberry@m	etrocast.net	_ Professional	license #:	PE 14243 LLS	80
Proposed project					
Number of proposed lots:	2; Are	there any pert	inent cover	nants? No	
Number of cubic yards of ea	arth being removed fror	n the site?0			
City water? yes X no _	; How far is City wa	ter from the sit	e? 20'		
City sewer? yes no	x; How far is City se	wer from the si	te? Over 1	500'	

Macintosh HD:Users:jaredrose:Desktop:Subdivision, Minor Application 4/11/2013

Updated

Continued Minor Subdivision Plan application Tax Map: 246	Lot: <u>27</u> Zone <u>R1</u>)
Wetlands: Is any fill proposed? NO; area to be filled:	; buffer impact?
Comments	,
Please feel free to add any comments, additional information	on, or requests for waivers here:
Submission of application	
This application must be signed by the property owner, app property owner), and/or the agent.	licant/developer (if different from
I (we) hereby submit this Subdivision application to the City pursuant to the City of Rochester Subdivision Regulations at knowledge all of the information on this application form and materials and documentation is true and accurate. As application or owner)/as agent, I attest that I am duly authorized in the commentation is true and country authorized in the commentation is true.	and attest that to the best of my d in the accompanying application cant/developer (if different from
Signature of property owner: Dad Com	
Date	D-10-18
Signature of applicant/developer:	
Signature of agent:	9:
Date	: 7-10-18
Authorization to enter subject property	
hereby authorize members of the Rochester Planning Boar Conservation Commission, Planning Department, and other oards and agencies to enter my property for the purpose of acluding performing any appropriate inspections during the cost-approval phase, construction phase, and occupancy phase if the performing and individuals legitimately involve aspecting this specific application/project. It is understood the passonable care, courtesy, and diligence when entering the performance of the property of the prop	pertinent City departments, i evaluating this application application phase, review phase, ase. This authorization applies d in evaluating, reviewing, or at these individuals must use all
ignature of property owner: Dand Cam	
Date: Page 2 (of 2 pages)	7-10-18
cintosh HD:Users:jaredrose:Desktop:Subdivision, Minor Application 1/2013	Updated

300 Sf		



BERRY SURVEYING & ENGINEERING

335 Second Crown Point Road Barrington, NH 03825 Phone: (603) 332-2863 Fax: (603) 335-4623 www.BerrySurveying.Com

City of Rochester Planning Board 33 Wakefield Street Rochester, NH 03867

Proposed Minor Subdivision

David & Destiny Groen

138 Chesley Hill Road, Rochester, N.H.

Narrative – Tax Map 246, Lot 27



On behalf of David & Destiny Groen, Berry Surveying & Engineering (BS&E) is filing a Minor Subdivision Application to subdivide Tax Map 103, Lot 94 into two separate lots.

Tax Map 246, Lot 27 is currently 419,902 SF, 9.63 Acres and is located in the R1 zone. It currently consists of a single family home with a septic system and a well. The applicant is looking to subdivide this into two lots which would support a proposed single family house and keep the remaining house on the smaller lot. These proposed lots meet the zoning requirements of the R1 zone. We have done a full boundary and topographical survey of the parcel. Stoney Ridge Environmental has flagged one area of wetlands on site and one small off site wetland, which we are holding buffers to.

The proposed driveway for lot 27-1 will impact the 50' wetland buffer. We are submitting a C.U.P. for that impact in conjunction with this subdivision application. The current house (lot 27) is on a septic system and well. We are proposing lot 27 stays on the current well until it stops producing. At that time they will tie into the municipal water system. Lot 27-1 will have its own well and septic system.

Respectfully Submitted,

BERRY SURVEYING & ENGINEERING

Christopher Berry Project Manager







Conditional Use Permit Application City of Rochester, New Hampshire

Property information
Tax map #: <u>246</u> ; Lot #('s): <u>27</u> ; Zoning district: <u>R1</u>
Property address/location: 138 Chesley Hill Rd
Name of project (if applicable): Proposed Subdivision for Groen
Property owner
Name (include name of individual): David & Destiny Groen
Mailing address: 138 Chesley Hill Rd, Rochester, NH 03839
Telephone #: _603-817-9354 Fax
Applicant/developer (if different from property owner)
Name (include name of individual): Same
Mailing address:
Telephone #: Fax #: Fax #:
Telephone #:Fax #: Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825 Telephone #: 603-332-2863 Fax #: 603-335-4623
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825 Telephone #: 603-332-2863 Fax #: 603-335-4623 Email address: K.Berry@BerrySurveying.com Professional license #: PE 14243 LLS 80 Proposed Project Please describe the proposed project: Proposing a driveway crossing through
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825 Felephone #: 603-332-2863 Fax #: 603-335-4623 Email address: K.Berry@BerrySurveying.com Professional license #: PE 14243 LLS 80
Engineer/designer Kenneth A Berry, PE, LLS Name (include name of individual): Berry Surveying & Engineering Mailing address: 335 Second Crown Point Rd, Barrington, NH 03825 Telephone #: 603-332-2863 Fax #: 603-335-4623 Email address: K.Berry@BerrySurveying.com Professional license #: PE 14243 LLS 80 Proposed Project Please describe the proposed project: Proposing a driveway crossing through

Please describe the existing conditions:	See attached narrative
Submission of application	
This application must be signed by the from property owner), and/or the agent.	property owner, applicant/developer (if different
knowledge all of the information on the application materials and documentation	e application to the City of Rochester Planning onling Ordinance and attest that to the best of my ais application form and in the accompanying is true and accurate. As applicant/developer (in attest that I am duly authorized to act in this latest that I am duly authorized to act in this
	Date:7-/0-18
Signature of applicant/developer:	
Signature of agent:	Date:
	Date: 7-10-18.





BERRY SURVEYING & ENGINEERING

335 Second Crown Point Road Barrington, NH 03825 Phone: (603) 332-2863 Fax: (603) 335-4623 www.BerrySurveying.Com crberry@metrocast.net

July 10, 2018

City of Rochester Planning Board Attention: Seth Creighton Chief Planner 33 Wakefield Street Rochester, NH 03867

RE: David & Destiny Groen Minor Subdivision 138 Chesley Hill Road Rochester, NH Tax Map 246, Lot 27 Conditional Use Permit

Mr. Chairman and Members of the Rochester Planning Board,

Enclosed are the criteria laid out in Chapter 42.21 for a conditional use permit as it pertains to the Conservation Overlay District (COD) in Chapter 42.12.

- A. Roads and other access ways; drainage ways; pipelines, power lines and other transmission lines; docks, boat launches, and piers; domestic water wells (and associated ancillary pipes and equipment); replacement septic tanks and leach fields where evidence is submitted that no alternative location is available on the property; provided that all of the following conditions are found to exist.
 - a. A wetland runs parallel to Chelsey Hill Road across the majority of the property. There is a small gap between the easterly boundary line that does not have wetlands but falls within the 50' wetland buffer. This is the only way to access the back 2/3's of the lot, which is currently underutilized.
- B. The proposed construction is essential to the productive use of land not within the CO District.
 - a. The rear 2/3's of the parcel is currently underutilized. Constructing the driveway within the 50' wetland buffer will allow the rear of the parcel (which is not within the CO district), to be utilized. Residential development will take place outside of the wetland buffers.

July 10, 2018

- C. Design and construction methods will be such as to minimize impact upon the wetlands and will include restoration of the site consistent with the permitted use.
 - a. Plans are included with the CUP application to show the limits and extent of the driveway construction. It was designed so that there would be a minimal effect on the wetland buffer and no impact on the wetlands. In addition, erosion and sediment control measures will be taken during construction to ensure no sediment or debris runs off into the wetlands. 2:1 slopes with stabilization matting is used to minimize impact.
- D. There is no feasible alternative route on land controlled by the applicant that does not cross the CO District nor has less detrimental impact on the wetlands. Nothing in this Section shall limit the applicant from exploring alternatives with abutting property owners.
 - a. The applicant has no other possible options to access the back of the lot within their land holdings and this was deemed the most efficient and effective to achieve access. Although it will encroach on a wetland buffer it proposes the least amount of disturbance, as it is the most direct route from Chesley Hill Road to the rear of the lot.
- E. Economic advantage is not the sole reason for the proposed location of the construction.
 - a. Economic advantage is not the sole reason for the proposed location. The applicant wants to further utilize the land and needs access to do so. Furthermore, the proposed road location is the only access point to the rear of the property that does not go directly through wetlands.

Included with this narrative is a scaled drawing that shows the limits of work within the 50' wetland buffer. This drawing should be used in relation to the provided plans. In addition to this drawing, several photographs are provided to show the existing state of the 50' wetland buffer and where the proposed driveway will go.

Respectfully Submitted,

Berry Surveying & Engineering

Christopher R. Berry Principal, President



BERRY SURVEYING & ENGINEERING

335 Second Crown Pt. Rd., Barrington, NH 03825 (603) 332-2863 / (603) 335-4623 FAX www.BerrySurveying.Com

July 10, 2018



Photograph #1: Standing on the existing trail at the edge of the wetlands, looking north towards the proposed driveway.

BERRY SURVEYING & ENGINEERING 335 Second Crown Pt. Rd., Barrington, NH 03825 (603) 332-2863 / (603) 335-4623 FAX www.BerrySurveying.Com



July 10, 2018




Ph



m MSL W6584 3m	Azimuth and Bearing (289° N18W		
3	7.6° -15° - 15° -		
otograph #2: Standing	g at traverse station 13 looking North West towards the proposed driveway.		
	BERRY SURVEYING & ENGINEERING 335 Second Crown Pt. Rd., Barrington, NH 03825		
RVEYING ENGINCERING	335 Second Crown Pt. Rd., Barrington, NH 03825 (603) 332-2863 / (603) 335-4623 FAX www.BerrySurveying.Com		

July 10, 2018




Photograph #3: Standing in the existing trail looking northeast.



BERRY SURVEYING & ENGINEERING 335 Second Crown Pt. Rd., Barrington, NH 03825 (603) 332-2863 / (603) 335-4623 FAX www.BerrySurveying.Com


July 10, 2018



Photograph #4: Standing in the proposed driveway looking at the edge of wetlands.





BERRY SURVEYING & ENGINEERING 335 Second Crown Pt. Rd., Barrington, NH 03825 (603) 332-2863 / (603) 335-4623 FAX www.BerrySurveying.Com





ROCHESTER, NH 03839 TAX MAP 246 LOT 27

1 IN. EQUALS 30 FT. DATE : JULY 10, 2018 FILE NO. : DB 2018 - 068











PROFILE VIEW PROPOSED DRIVEWAY 4+50-END





NOTES:

1.) OWNER: DAVID & DESTINY GROEN 138 CHESLEY HILL ROAD ROCHESTER, NH 03839


a.) TAX MAP 246, LOT 27

b.) EXISTING LOT AREA: 419,902 Sq.Ft., 9.83 Ac. PROPOSED LOT AREAS: LOT 27: 74,185 Sq.Ft., 1.70 Ac.

LOT 27-1; 345,717 Sq.Ft., 7.93 Ac.

- 2.) THE PURPOSE OF THIS PLAN IS TO DEMONSTRATE THE SITE PLAN, GRADING, AND PROPER EROSION AND SEDIMENT CONTROL DURING CONSTRUCTION PRACTICES.
- 3.) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVE AND BELOW GROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR. ANY UTILITY CONFLICTS SHOULD BE REPORTED IMMEDIATELY TO THE DESIGN ENGINEER.
- THE CONTRACTOR SHALL CALL AND COORDINATE WITH DIGSAFE 1-888-344-7233 AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE
- 5.) SEE DETAILS CONCERNING SITE LAYOUT, DRAINAGE, UTILITY AND SEDIMENT AND EROSION CONTROLS.
- 6.) ALL DRAINAGE PIPE IS TO BE HDPE N-12. INDIVIDUAL PIPE SIZES ARE SPECIFIED ON GRADING AND DETAIL PLAN SHEETS.
- ALL ELEVATIONS TO BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. THE DESIGN ENGINEER IS TO BE NOTIFIED IMMEDIATELY OF ANY DISCREPANCY. TEMPORARY BENCHMARKS (T.B.M.) ARE TO BE PROVIDED BY THE DESIGN ENGINEER.
- UPON FINAL COMPLETION AND 85% STABILIZATION, THE DRAINAGE SYSTEM IS TO BE CLEANED OF ALL DEBRIS. SEDIMENT CONTROL PRACTICES REMOVED AND DISPOSED OF PROPERLY, AND ANNUAL MAINTENANCE PREFORMED ON ALL DRAINAGE PRACTICES.
- 9.) ALL UNPAVED AREAS ARE TO RECEIVE 4" QUALITY LOAM AND SEED.
- 10.) SILT FENCE MAY BE SUBSTITUTED WITH SILT SOXX OR EROSION CONTROL MIX BERM. SILT FENCE IS NOT A SUBSTITUTE FOR SILT SOXX, OR APPROVED EQUAL
- 11.) DURING LOT DEVELOPMENT, THE BUILDERS ARE TO ENSURE NO TRACKING TAKES PLACES WITHIN THE DRIVEWAY, THAT RESIDENTIAL WASTE IS TAKEN CARE OF, AND GENERAL CLEAN UP & HOUSE KEEPING ITEMS ARE ADHERED TO.
- 12.) SILT SOCK AND SILT FENCE MAY BE REPLACED WITH MULCH BERM PER THE CONSTRUCTION DETAILS.
- 13.) DRAINAGE TO BE TAKEN INTO CONSIDERATION AT THE TIME OF HOUSE/GARAGE GRADING AND SEPTIC DESIGN.





DESCRIPTION	
DATE	
REVISION	


DRIVE ROFILE PROPOSED I
LAND OF
DAVID & DESTINY G
138 CHESLEY HILL I
ROCHESTER, NH 03
TAX MAP 246 LO


335 BARRING SCALE DATE :



SHEET 2 OF 5

BE





- PROVED CONSTITUTION SPECIFICATIONS
 WOVEN WRE FENCE TO BE FASTENED SECURELY TO FENCE POSTS WITH WIRE TIES OR STAPLES
 AND FILTER CLOTH SHALL BE FASTENED TO WOVEN WIRE EVERY 24" AT TOP MID AND BOTTOM
 SECTIONS AND BE EMBEDDED INTO GROUND A MINIMUM OF 8" THE FENCE POSTS SHALL BE A MINIMUM 48" LONG, SPACED A MAXIMUM 10' APART, AND DRIVEN A MINIMUM OF 16" INTO THE
- WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER. THE ENDS OF THE FABRIC SHALL BE WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER, THE ENDS OF THE FABRIC SHALL BE OVERLAPPED BY SIX NOHES, FOLDED AND STAPLED TO PREVENT SEDIMENT FROM BY-PASSING. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND SEDIMENT REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE AND PROPERLY DISPOSED OF. SEE MAINTENANCE NOTE BELOW, REMOVAL OF SEDIMENT REQUIRED AT A DEPTH OF 6-INCHED. PLACE THE ENDS OF THE SILT FENCE UP CONTOUR TO PROVIDE FOR SEDIMENT STORAGE. SILT FENCES SHALL BE REMOVED WHEN NO LONGER NEEDED AND THE SEDIMENT COLLECTED SHALL BE DISPOSED AS DIRECTED BY THE ENGINEER.

 THE AREA DISTURBED BY THE REMOVAL SHALL BE SMOOTHED AND RE-VEGETATED.

 TO BE CONSTRUCTED IAW NH SWM #3 4-2 SEDIMENT CONTROL PRACTICES, SILT FENCE, PAGE 90.

- SILT FENCE MAINTENANCE SILT FENCES SHALL BE INSPECTED IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REPAIRS THAT ARE REQUIRED SHALL BE MADE
- IMMEDIATELY.

 IF THE FABRIC ON A SILT FENCE SHOULD DECOMPOSE OR BECOME INEFFECTIVE DURING THE EXPECTED LIFE OF THE FENCE, THE FABRIC SHALL BE REPLACED PROMPTLY.

 3. SEDIMENT DEPOSITS SHOULD BE REMOVED WHEN THEY REACH SIX—INCHES IN DEPTH.

 4. SEDIMENT DEPOSITS THAT ARE REMOVED OR LEFT IN PLACE AFTER THE FABRIC HAS BEEN REMOVED SHALL BE GRADED TO CONFORM WITH THE EXISTING TOPOGRAPHY AND VECETATED.


SILT FENCE DETAIL
NOT TO SCALE

E5

E9

d50 SIZE=	0.5	FEET	6	INCHES
% OF WEIGHT S THAN THE GIVE		SIZE (FROM)F STON	IE (INCHES) TO
100%		9		12
85%		8		11
50%		6		9
15%		2		3

CONSTRUCTION SAFETY FENCE



1. ALL SPISTIME AREAS SHALL BE PROTECTED AS PER PLAN.

2. ALL TREES IN THE CONSTRUCTION AREA NOT SPISCEPLALY DESIDNATED FOR REMOVAL SHALL BE PRESENTED AND PROTECTED WITH 16th VISSBUTLY FENCE AS PER PLAN.

3. WHEN PRACTIONALS, RISTALL, MEN VISSBUTLY SHOULD COUNTRY OF THE ORP LINE OF THE TREE.

4. SMETT YENCE SWOLD BE FASTERIED SECURELY TO THE FORTS.

4. SMETT YENCE SWOLD BE FASTERIED SECURELY TO THE FORTS.

PROTECTIVE FEDURIOR MUST BE APPROVED.

2'-0" MIN.

THE BERMS SHALL BE INSTALLED ON SLOPES LESS THAN 5%.

EROSION CONTROL MIX BERMS SHALL BE USED ONLY AS FOLLOWS:

1. BERMS SHALL BE USED IN AREAS WHERE EROSION WILL OCCUR ONLY IN THE FORM OF SHEET EROSION AND THERE IS NO CONCENTRATION OF WATER IN A CHANNEL OR DRAINAGE WAY ABOVE THE BERM.

2. THE BERMS SHALL BE INSTALLED FOLLOWING THE CONTOUR OF THE LAND AS CLOSLY AS

THE BERMS SHALL BE INSTALLED ON SLOPES LESS THAN 5% SUBJECT TO (€), BELOW, THE MIX SHALL HAVE AN ORGANIC PORTION BETWEEN 80 AND 100%, DRY WEIGHT BASIS, AND BE FIBROUS AND ELONGATED SUCH AS FROM SHREDDED BARK, STUMP GRINDINGS, COMPOSED BARK, OR COUNVALENT MANUFACTURED PRODUCTS. WOOD AND BARK CHIPS, GROUND CONSTRUCTION DEBRIS, OR REPROCESSED WOOD PRODUCTS SHALL NOT BE USED AS ORGANIC MATERIAL. THE MIX SHALL NOT CONTAIN SILTS, CLAY, OR FINE SANDS.

THE MIX SHALL HAVE A PARTICLE SIZE BY WEIGHT OF 70 TO 85% PASSING A 6-INCH SCREEN. THE MIX SHALL HAVE A PERTICLE SIZE BY WEIGHT OF 70 TO 85% PASSING A 6-INCH SCREEN AND A MAXIMUM OF 85% PASSING THE 0.75-INCH SCREEN. THE MIX SHALL BE AT LEAST 12 INCHES HIGH AND AT LEAST 2 FEET WIDE. TO BE CONSTRUCTED IAW NH SWM

#3 4-2 SEDIMENT CONTROL PRACTICES, EROSION CONTROL MIX BERMS, PAGE 106.

CONSTRUCT AT ANGLE OF REPOSE

EXISTING


GRADE

EROSION CONTROL MIX BERM

EROSION CONTROL MIX

1'-0" MIN.

E3STABILIZED CONSTRUCTION ENTRANCE



- PLAN VIEW

 1. STONE FOR A STABILIZED CONSTRUCTION ENTRANCE SHALL BE 3 INCH STONE, RECLAIMED STONE, OR RECYCLED CONCRETE COUNTALENT.

 2. THE LENGTH OF THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 75 FEET, EXCEPT THAT THE MINIMUM LENGTH MAY BE REDUCED TO 50 FEET IF A 3—INCH TO 6—INCH BERM IS INSTALLED AT THE ENTRANCE OF THE PROJECT SITE.

 3. THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6 INCHES.

 4. THE WIDTH OF THE ENTRANCE SHALL NOT BE LESS THAN THE FULL WIDTH OF THE ENTRANCE WHERE INGRESS OR CERESS OCCURS OR 10 FEET, WHICH EVER IS GREATER.

 5. GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING C. ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION ENTRANCE SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERN WITH 5:1 SLOPES THAT CAN BE GROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE.

 7. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS—OF—WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEAN OUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SKILLED, WASHED, OR TRACKED ONTO PUBLIC RICH OF THE OWNER OF SEDIMENT MUST BE REDUCED FROMPILY.

 8. TO BE CONSTRUCTED IAW NH SIMM \$3 4–2 SEDIMENT CONTROL PRACTICES, TEMPORARY CONSTRUCTION EXT, PAGE 124.

DEFINITION OF STABLE:

BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED. A MINIMUM OF 85 PERCENT VEGETATED GROWTH HAS BEEN ESTABLISHED. A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIP-RAP HAS BEEN INSTALLED. OR, EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.

HAY MULCH OR OTHER APPROVED METHODS SHALL BE USED TO CONTROL EROSION OF NEWLY GRADED AREAS. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED WITHIN 72 HOURS AFTER THEIR CONSTRUCTION. CITY OF ROCHESTER CHAPTER 50: DISTURBED SOIL AREAS SHALL BE EITHER TEMPORARILY OR PERMANENTLY STABILIZED. IN AREAS WHERE FINAL GRADING HAS NOT OCCURRED, TEMPORARY STABILIZED. IN AREAS WHERE FINAL GRADING HAS NOT OCCURRED, TEMPORARY STABILIZATION MEASURES SHOULD BE IN PLACE WITHIN SEVEN (1) CALENDAR DAYS FOR EXPOSED SOIL AREAS THAT ARE WITHIN ONE HUNDRED (100) FEET OF A SUFFACE WATER BODY OR A WETLAND AND NO MORE THAN 14 CALENDAR DAYS FOR ALL OTHER AREAS, PERMANENT STABILIZATION SHOULD BE IN PLACE WITHIN THREE (3) CALENDAR DAYS FOLLOWING COMPLETION OF FINAL GRADING OF EXPOSED SOIL AREAS.

PER ENV-WQ 1500 ALTERATION OF TERRAIN

ADDITION STABILIZATION NOTES:

E7

XISTING TIONS AL

INTO


KEY F

E4

CASTINGS ARE RATED FOR H20 WHEEL LOAD TRAFFIC PAINT: CASTINGS ARE FURNISHED WITH A BLACK PAINT

12" CAST IRON GRATE NOT TO SCALE





TEMPORARY EROSION CONTROL MEASURES

- 1. THE SMALLEST PRACTICAL AREA OF LAND SHALL BE EXPOSED AT ANY ONE TIME.
- 2. EROSION, SEDIMENT AND DETENTION MEASURES SHALL BE INSTALLED AS SHOWN ON THE PLANS AND AT LOCATIONS AS REQUIRED, DIRECTED BY THE ENGINEER.
- ALL DISTURBED AREAS SHALL BE RETURNED TO ORIGINAL GRADES AND ELEVATIONS. DISTURBED AREAS SHALL BE LOANED WITH A MININUM OF 4" OF LOAM AND SEEDED WITH NOT LESS THAN ONE POUND OF SEED PER 50 SQUARE VARDS OF AREA (SEE SEED SPECIFICATIONS THIS SHEET)
- ALL DISTURBED AREAS WILL BE RESTABILIZED WITHIN 45 DAYS. AT ANY ONE TIME, NO MORE THAN 5 ACRES, (217,800 Sq. Ft.) WILL BE DISTURBED.
- SILT FENCES AND PERIMETER BARRIERS SHALL BE INSPECTED PERIODICALLY AND AFTER EVERY RAIN DURING THE LIFE OF THE PROJECT. ALL DAMAGED AREAS SHALL BE REPAIRED, SEDIMENT DEPOSITS SHALL PERIODICALLY BE REMOVED AND DISPOSED OF.
- AFTER ALL DISTURBED AREAS HAVE BEEN STABILIZED, THE TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES ARE TO BE REMOVED AND THE AREA DISTURBED BY THE REMOVAL SMOOTHED AND RE-YECTATED.
- PER THE EPA CGP REQUIREMENTS THERE WILL BE REPORTS OF THE EROSION CONTROL INSPECTIONS US WAPPP PREPARED BY 98-EE. ALL EROSION CONTROLS SHALL BE INSPECTED WEEKLY AND WITHIN 24 HOURS AFTER 0.5" OR GREATER RAIN EVENT.
- 8. DITCHES, SWALES, AND BASINS SHALL BE STABILIZED PRIOR TO DIRECTING RUNOFF TO THEM.
- DO NOT TRAFFIC EXPOSED SOIL SURFACES WITH CONSTRUCTION EQUIPMENT. IF FEASIBLE, PERFORM EXCAVATIONS WITH EQUIPMENT POSITIONED OUTSIDE THE LIMITS OF THE INFILTRATION SYSTEM.
- 10. DRIVEWAYS AND CUT AND FILL SPLOPES MUST BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINAL GRADE.
- 11. STABILIZATION MEANS
- A MINIMUM OF 85% OF VEGETATIVE COVER HAS BEEN ESTABLISHED.
 A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIP RAP HAS BEEN INSTALLED, OR
 CROSION CONTROL BLANKETS HAVE BEEN INSTALLED.
- 12. THIS PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.
- 13. THE NHDES STORMWATER MANUAL, IN THREE VOLUMES, DATED DECEMBER 2008, IS A PART OF THIS PLAN SET AND THE MORE RESTRICTIVE WILL GOVERN. (NH SWM)

LAND OF DAVID & DESTINY 138 CHESLEY HILL ROCHESTER, NH (

YING INEERING POINT ROAD 5 (603)332–28 URVEY ENGII CROWN F S

335 BARRING NEW A KENNET


LICENSED! SHEET 4 OF 5

THE DISTANCE SUCH THAT POINTS A AND B ARE OF EQUAL ELEVATION. NOT TO SCALE

SPACING BETWEEN STRUCTURES

- 1.) CHECK DAMS SHOULD BE INSTALLED BEFORE RUNOFF IS DIRECTED TO THE SWALE OR DRAINAGE DITCH.
 2.) THE MAXIMUM CONTRIBUTING DRAINAGE AREA TO THE DAM SHOULD BE LESS THEN ONE AREA.
 3.) THE MAXIMUM HEIGHT OF THE DAM SHOULD BE TWO FEET.
 4.) THE CENTER OF THE DAM SHOULD BE AT LEAST SIX INCHES LOWER THAN THE OUTER EDGES.
 5.) THE MAXIMUM SPACING IS AS SHOWN ON THE PROJECT SITE PLANS.
- PLANS.
 CHECK DAMS WILL NOT BE USED IN A FLOWING STREAM.
 TEMPORARY CHECK DAMS WILL BE REMOVED ONCE THE
 SWALE OR DITCH IS DETERMINED STABLE.
- 8.) TO BE CONSTRUCTED IAW NH SWM #3 4-2 SEDIMENT CONTROL PRACTICES, TEMPORARY CHECK DAMS, PAGE 114.

NOTE: KEY STONE INTO CHANNEL BANKS AND EXTEND IT BEYOND THABUTMENTS A MINIUM OF 18" TO PREVENT FLOW AROUND THE DAM.



2"X2"X36" WOODEN STAKES PLACED 10' O.C. (SEE SECTION) E10 应 -FILTREXX SOXX (12" TYPICAL) AREA TO BE PROTECTED WATER FLOW WORK AREA

. ISS.

ALL MATERIAL TO MEET FILTREXX SPECIFICATIONS.

FILTER MEDIA FILL TO MEET APPLICATION REQUIRENTS.

COMPOST MATERIAL TO BE DISPERSED ON SITE, AS DETERMINED BY ENGINEER.

SILTSOXX MAY BE USED IN PLACE OF SILT FENCE OR OTHER SEDIMENT

- BARRIERS.
 SILTSOXX COMPOST/SOIL/ROCK/SEED FILL MATERIAL SHALL BE ADJUSTED AS NECESSARY TO MEET THE REQUIRMENTS OF THE SPECIFIC APPLICATION, FILTREXX SOXX IS A REGISTREED TRADBLARK OF FILTREXXON TERMATIONAL, LLC. SILT FENCE IS NOT A SUBSTITUTION FOR SILT SOXX AND ANY EQUAL SUBSTITUTION TO BE APPROVED.
 TO BE CONSTRUCTED IAW FILTREXX, SECTION 1:EROSION & SEDIMENT CONTROL (PAGE 323) CONSTRUCTION ACTIVITIES, SWPPP CUT SHEET: FILTREXX SEDIMENT CONTROL

FILTREXX SEDIMENT <u>CONTROL</u> NOT TO SCALE 3.0' 2"X2"X36" WOODEN STAKES PLACED 10' O.C. -FILTREXX SOXX BLOWN /PLACED FILTER MEDIA-AS NOTED) AREA TO BE PROTECTED American maning WORK AREA

OR APPROVED EQUAL

E-101

 \underline{PLAN} not to scale Filtrexx International, LLC 35481 Grafton Eastern Rd | Grafton, Oh 44044 440-926-2607 | fax: 440-926-4021 WWW.FLLTREXX.COM

NOTE: FOR AREAS REQUIRING DOUBLE PERIMETER CONTROL WITHIN 50' OF JURISDICTIONAL WETLANDS AND NOT FOR ALL SILT SOXX APPLICATIONS. THIS DUPLICATION MAY BE SPECIFIED AS 12" SILT SOXX OR ORANGE CONSTRUCTION FENCE AS NOTED.

 $\underline{SECTION}$ NOT TO SCALE

S = &C SECOND C TON, NH AS NO JULY 10 ERRY DATE FILE 1 $\overline{\mathbf{m}}$

STONE CHECK DAM

CONSTRUCTION SEQUENCE:

- 1.) CUT AND REMOVE TREES IN CONSTRUCTION AREA ONLY AS REQUIRED, RELOCATE ANY PROJECT T.B.M.
- 2.) CONSTRUCT AND/OR INSTALL TEMPORARY AND PERMANENT SEDIMENT EROSION AND DETENTION CONTROL FACILITIES AS SPECIFED, EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSTALLED PRIOR TO ANY SOIL LAND DISTURBANCE AND MUST BE REMEMBED AND APPROVED BY THE COMMUNITY SERVICES EPERATURY.
- EROSION, SEDIMENT AND DETENTION CONTROL FACILITY SHALL BE INSTALLED & STABILIZED PRIOR TO DIRECTING RUNOFF TO THEM. TEMPORARY DIVERSIONS MAY BE REQUIRED. POST CONSTRUCTION STORM WATER MANAGEMENT PRACTICES MUST BE INITIATED AND STABILIZED EARLY IN THE PROCESS.
- 4.) CLEAR, CUT AND DISPOSE OF DEBRIS IN APPROVED FACILITY
- 5.) CONSTRUCT TEMPORARY CULVERTS AS REQUIRED, OR DIRECTED
- 6.) CONSTRUCT ROADWAYS FOR ACCESS TO DESIRED CONSTRUCTION AREAS, ALL ROADS SHALL BE STABILIZED IMMEDIATELY
- 7.) START BUILDING CONSTRUCTION
- 8.) INSTALL PIPE AND CONSTRUCTION ASSOCIATED APPURTENANCES AS REQUIRED OR DIRECTED. INSTALL RAIN GARDENS. ALLDISTURBED AREAS SHALL STABILIZED IMMEDIATELY AFTER GRADING.
- 9.) BEGIN PERMANENT AND TEMPORARY SEEDING AND MULCHING. ALL CUT AND FILL SLOPES AND DISTURBED AREAS SHALL BE SEEDED OR MULCHED AS REQUIRED. OR DIRECTED. NO AREA IS ALLOWED TO BE DISTURBED FOR A LENGTH OF TIME THAT EXCEDS 60 DAYS BEFORE. BEING STABILIZED, DALLY, OR AS REQUIRED. ALL ROADWAYS AND PARKING AREAS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING PRISHED GRADES. ALL CUT AND FILL SLOPES SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING PRISHED GRADES.
- 10.) CONSTRUCT TEMPORARY BERMS, DRAINS DITCHES, SILT FENCES, SEDIMENT TRAPS, ETC. MULCH AND SEED AS REQUIRED.
- 11.) INSPECT AND MAINTAIN ALL EROSION AND SEDIMENT CONTROL MEASURES DURING CONSTRUCTION. ALL SWPPP INSPECTIONS MUST BE CONDUCTED BY A QUALIFIED PROFESSIONAL SUCH AS A PROFESSIONAL ENGINEER (PE). A CERTIFED PROFESSIONAL IN EROSION AND SEDIMENT CONTROL (CPESC), A CERTIFIED EROSION SEDIMENT AND STORM WATER INSPECTOR (CESSWI), OR A CERTIFIED PROFESSIONAL STORM WATER QUALITY (CPSWO). INSPECTION REPORTS SHALL BE SUBMITTED TO THE COMMUNITY SERVICES DEPARTMENT.
- 12.) COMPLETE PERMANENT SEEDING AND LANDSCAPING.
- 13.) REMOVE TEMPORARY EROSION CONTROL MEASURES AFTER SEEDING AREAS HAVE ESTABLISHED THEMSELVES AND SITE IMPROVEMENTS ARE COMPLETE.
- 14.) SMOOTH AND REVEGETATE ALL DISTURBED AREAS.
- 15.) FINISH PAVING ALL ROADWAYS.

E13

WINTER STABILIZATION NOTES


1. ALL DISTURBED AREAS THAT DO NOT HAVE AT LEAST 85% VEGETATIVE COVERAGE PRIOR TO OCTOBER 15TH SHALL BE STABILIZED BY APPLYING MULCH AT A RATE OF 3-4 TONS PER ACRE. ALL SIDE SLOPES, STEEPER THAN 4:1, THAT ARE NOT DIRECTED TO SWALES OR DETENTION BASINS, SHALL BE LINED WITH BIODEGRADABLE/PHOTOGEGRADABLE "JUTE MATTING" (EXCCESSOR'S CURLEX II OR EQUAL). ALL OTHER SLOPES SHALL BE MULCHED AND TACKED AT A RATE OF 3-4 TONS PER ACRE. THE APPLICATION OF MULCH AND/OR JUTE MATTING SHALL NOT OCCUR OVER EXISTING SNOW COVER. IF THE SITE IS ACTIVE AFTER NOVEMBER 15TH, ANY SNOW THAT ACCUMULATES ON DISTURBED AREAS SHALL BE REMOVED. PRIOR TO SPRING THAW ALL AREAS WILL BE STABILIZED, AS DIRECTED ABOVE.

2. ALL SWALES THAT DO NOT HAVE FULLY ESTABLISHED VEGETATION SHALL BE EITHER LINED WITH TEMPORARY JUTE MATTING OR TEMPORARY STONE CHECK DAMS (APPROPRIATELY SPACED). STONE CHECK DAMS WILL BE MAINTAINED THROUGHOUT THE WINTER MONTHS. IF THE SWALES ARE TO BE MATTED WITH PERMANENT LINERS OR RIPRAP WITH ENGINEERING FABRIC, THIS SHALL BE COMPLETED PRIOR TO WINTER SHUTDOWN OR AS SOON AS THEY ARE PROPERTY GRADED AND SHAPED.


3. PRIOR TO NOV. 15TH ALL ROADWAY AND PARKING AREAS SHALL BE BROUGHT UP TO AND THROUGH THE BANK RUN GRAVEL APPLICATION. IF THESE AREAS' ELEVATIONS ARE PROPOSED TO REMAIN BELOW THE PROPOSED SUBGRADE ELEVATION, THE SUBGRADE MATERIAL SHALL BE ROUGHLY CROWNED AND A 3" LAYER OF CRUSHED GRAVEL SHALL BE PLACED AND COMPACTED. THIS WILL ALLOW THE SUBGRADE TO SHED RUNOFF AND WILL REDUCE ROADWAY EROSION. THIS CRUSHED GRAVEL DOES NOT HAVE TO CONFORM TO NH DOT 304.3, BUT SHALL HAVE BETWEEN 15-25% PASSING THE #200 SIEVE AND THE LARGEST STONE SIZE SHALL BE 2". IF THE SITE IS ACTIVE AFTER NOVEMBER 15TH, ANY ACCUMULATED SNOW SHALL BE REMOVED FROM ALL ROADWAY AND PARKING AREAS.

4. AFTER OCTOBER 15TH, THE END OF NEW HAMPSHIRE'S AVERAGE GROWING SEASON, NO ADDITIONAL LOAM SHALL BE SPREAD ON SIDE SLOPES AND SWALES. THE STOCKPILES THAT MILL BE LEFT UNDISTURBED UNTIL SPRING SHALL BE SEEDED BY THIS DATE. AFTER OCTOBER 15TH, ANY NEW OR DISTURBED PILES SHALL BE MULCHED AT A RATE OF 3-4 TONS PER ACRE. ALL STOCKPILES THAT WILL REMAIN THROUGHOUT THE WINTER SHALL BE SURROUNDED WITH SILT FENCING.

E16



BITUMINOUS CONCRETE PAVEMENT SECTION



PIPE OUTLET PROTECTION CONSTRUCTION SPECIFICATIONS

BE PREPARED TO THE LINES AND GRADES SHOWN ON THE PLANS. SPECIFIED GRADATION. 2. THE ROCK OR GRAVEL USED FOR FILTER OF RIP RAP SHALL CONFORM TO NHDOT

1. THE SUB GRADE FOR THE FILTER MATERIAL, GEOTEXTILE FABRIC, AND RIP RAP SHALL

5. GEOTEXTILE FABRICS SHALL BE PROTECTED FROM PUNCTURE OR TEARING DURING THE PLACEMENT OF THE ROCK RIP RAP DAMAGED AREAS IN THE FABRIC SHALL BE REPAIRED BY PLACING A PIECE OF FABRIC OVER THE DAMAGED AREA OR BY COMPLETE REPLACEMENT OF THE FABRIC ALL OVERLAPS REQUIRED FOR REPAIRS OR JOINING TWO PIECES OF FABRIC SHALL BE A MINIMUM OF 12 INCHES.

4. STONE FOR THE RIP RAP MAY BE PLACED BY EQUIPMENT AND SHALL BE CONSTRUCTED TO THE FULL LAYER THICKNESS IN ONE OPERATION AND IN SUCH A MANNER AS TO PREVENT SEGREGATION OF THE STONE SIZES.

5. TO BE CONSTRUCTED IAW NH SWM #2 4-6 CONVEYANCE PRACTICES, 6. OUTLET PROTECTION, PAGE 172.

PIPE OUTLET TO WELL-DEFINED CHANNEL WITH NO DEFINED CHANNEL


E14

NOTE: THIS PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

SEEDING RATES

POUNDS POUNDS PER PER ACRE 1,000 So. Ft.

NOTE: Temporary seed mix for stabilization of turf shall be winter rye or oats at a rate of 2.5 lbs. per 1000 s.f. and shall be placed prior to OCT. 15, if permanent seading not wet complete.



TALL FESCUE CREEPING RED FESCUE RED TOP TOTAL 0.45 0.45 0.05 TALL FESCUE CREEPING RED I CROWN VETCH DR FLAT PEA TOTAL 15 10 0.35 40 0R 55 0.95 OR 1.35 TALL FESCUE CREEPING RED FESCUE BIRDS FOOT TREFOIL TOTAL TALL FESCUE FLAT PEA TOTAL 20 30 50 CREEPING RED FESCUE 1/ 50 KENTUCKY BLUEGRASS 1/ 50

MOCTURE

NSERVATION MIX	POUNDS PER ACRE	POUNDS PE 1,000 S.F.
D FESCUE (35%)	75	1.75
LL FESCUE (25%)	55	1.25
NUAL RYEGRASS (12%)	33	0.75
RENNIAL RYEGRASS (10%)	26	0.60
NTUCKY BLUEGRASS (10%)	22	0.50
HTE CLOVER (3%)	7	0.15
NTUCKY BLUEGRASS (10%)		0.50

E15 4" TOPSOIL (MIN.) AND SEED TO ESTABLISH INSTALL ROLLED FROSION CONTROL BLANKET WITH ANCHOR HOOKS AS PER MANUFACTURES REQUIREMENTS. SUBMIT SHOP DRAWINGS FOR APPROVAL RODUCT EXAMPLES ANCHOR HOOK PER 2.) NAG BIONET SC 150 BN 2:1 TO 1:1 SLOPE MANUFACTURER'S REQUIREMENTS 3.) NAG BIONET SC 125 BN 1:1 AND GREATER 4.) AEC CURLEX II 1,5H TO 1V TO BE CONSTRUCTED IAW NH SWM #3 4-1 EROSION CONTROL PRACTICES, TEMPORARY EROSION CONTROL BLANKET, PAGE 68.
ANCHOR PATIENT AND INSTALLATION INSTRUCTIONS FROM NORTH AMERICAN GREEN (NAG) AND AMERICAN EROSION COMPANY (AEC) WILL BE FOLLOWED FOR EACH APPLICATION AND SLOPE COMPITIONS WILL APPLY.

> ROLLED EROSION CONTROL BLANKET (RECB) SLOPE STABILIZATION DETAIL

NOT TO SCALE

- GRADING AND SHAPING A. SLOPES SHALL NOT BE STEEPER THAN 2:1; 3:1 SLOPES OR FLATTER ARE

SEEDING SPECIFICATIONS

- A SLOPES SHALL NOT BE STEEPER HAM 2:1;3:1 SLOPES OR FLATTER ARE.
 PREFERRED.
 WHERE MOWING WILL BE DONE, 3:1 SLOPES OR FLATTER ARE RECOMMENDED.
 SEEDBED PREPARATION
 A. SURFACE AND SEEPAGE WATER SHOULD BE DRAINED OR DIVERTED FROM
 THE SITE TO PREVENT DROWNING OR WINTER KILLING OF THE PLANTS.
 B. STONES LARGER THAN 4 INCHES AND TRASH SHOULD BE REMOVED BECAUSE.
 THEY INTERFERE WITH SEEDING AND FUTURE MAINTENANCE OF THE AREA. WHERE
 FEASBIEL, THE SOIL SHOULD BE TILLED TO A DEPTH OF ABOUT 4 INCHES TO
 PREPARE A SEED BED AND MIX FERTILIZER AND LIME INTO THE SOIL THE SEEDBED.
 SHOULD BE IFFT IN PRESONABLY FIRM AND SMOOTH CONDITION THE LAST TILLAGE. SHOULD BE LEFT IN REASONABLY FIRM AND SMOOTH CONDITION. THE LAST TILLAGE OPERATION SHOULD BE PERFORMED ACROSS THE SLOPE WHEREVER PRACTICAL.
- ESTABLISHING A STAND A. LIME AND FERTILIZER SHOULD BE APPLIED PRIOR TO OR AT THE TIME OF
- AND INCORPORATED INTO THE SOIL KINDS AND AMOUNTS OF LIME AND FERTILIZER SHOULD BE BASED ON AN EVALUATION OF SOIL TESTS. WHEN A SOIL TEST IS NOT AVAILABLE,
- THE FOLLOWING MINIMUM AMOUNTS SHOULD BE APPLIED: AGRICULTURAL LIMESTONE, 2 TONS PER ACRE OR 100LBS, PER 1,000 SQ.FT. NITROGEN(N), 50LBS. PER ACRE OR 1.1LBS. PER 1,000 SQ.FT. PHOSPHATE(P205), 100LBS. PER ACRE OR 2.2LBS. PER 1,000 SQ.FT. POTASH(K20), 100LBS, PER ACRE OR 2,2LBS, PER 1,000 SQ.FT. (NOTE: THIS IS THE EQUIVALENT OF 500LBS, PER ACRE OF 10-20-20 FERTILIZER OR 1,000LBS. PER ACRE OF 5-10-10.)
- B. SEED SHOULD BE SPREAD UNIFORMLY BY THE METHOD MOST APPROPRIATE FOR THE SITE. B. SEED SHOULD BE SPREAD UNFORMET BY IT HE MELHOU MUST APPROPRIATE FOR HE STE. METHODS INCLUDE BROADCASTING, DRILLING AND HYDROSEDIUM, WHERE BROADCASTING IS USED, COVER SEED WITH 25 INCH OF SOLIO OR LESS, BY CULTIFACKING OR RAKING. C. REFER TO TABLE(G-ET THIS SHEET) FOR APPROPRIATE SEED MIXTURES AND TABLE(H-ET THIS SHEET) FOR RATES OF SEEDIMG. ALL LEGUMES (GROWN/ETCH, BIRDSFOOT TREFOIL, AND FLATTER) MUST BE INCOLULATED WITH THEIR SPECIFIC INCOLLAND.
- D. WHEN SEEDED AREAS ARE MULCHED, PLANTINGS MAY BE MADE FROM EARLY SPRING TO EARLY OCTOBER. WHEN SEEDED AREAS ARE NOT MULCHED, PLANTINGS SHOULD BE MADE FROM EARLY SPRING TO MAY 20 OR FROM AUGUST 10 TO SEPTEMBER 1
- A. HAY, STRAW, OR OTHER MULCH, WHEN NEEDED, SHOULD BE APPLIED IMMEDIATELY AFTER
- SELDING.

 B. MULCH WILL BE HELD IN PLACE USING APPROPRIATE TECHNIQUES FROM THE BEST MANAGEMENT PRACTICE FOR MULCHING, HAY OR STRAW MULCH SHALL BE PLACED AT A RATE OF 90LBS PER 1000 S.F.
- 1000 S.F.

 MAINTENANCE TO ESTABLISH A STAND

 A. PLANIED AREA SHOULD BE PROTECTED FROM DAMAGE BY FIRE, GRAZING, TRAFFIC, AND DENSE
 WEED GROWTH.

 B. FERTILIZATION NEEDS SHOULD BE DETERMINED BY ONSITE INSPECTIONS. SUPPLEMENTAL
 FERTILIZER IS USUALLY THE KEY TO FULLY COMPLETE THE ESTABLISHMENT OF THE STAND
 BECAUSE MOST PERENNIAL STAKE 2 TO 3 YEARS TO BECOME STABLISHED.

 C. IN WATERWAYS, CHANNELS, OR SWALES WHERE UNIFORM FLOW CONDITIONS ARE ANTICIPATED,
 OCCASIONAL MOWING MAY BE NECESSARY TO CONTROL GROWTH OF WOODY VEGETATION.

 TO BE CONSTRUCTED LAW NH SWM #3 4—1 EROSION CONTROL PRACTICES, PERMANENT
 VEGETATION, PAGE 60.

E18


DIAMETER	12"	15"	18"	24"	30"
LENGTH	3'-2"	3'10"	5'-2"	7'-2"	9'-2"
CONC. (Cu.Yd.)	0.61	0.85	1.13	1.78	2.58
STEEL (Lbs.)	9	11	14	20	25

ALL STEEL SHALL BE #5 REINFORCING STEEL, SPACED @ 12" ON CENTER SEE NHDOT DETAIL HW-1

E17 UNPAVED | PAVED SEE PERMANENT PAVEMENT
PATCH DETAIL OR TYPICAL
PAVEMENT SECTION DETAIL
FOR PAVEMENT AND GRAVEL
REQUIREMENTS 4" TOPSOIL AND SEED (TYP) -COMMON FILL (SUITABLE MATERIAL FROM EXCAVATION) COVER FOR DRAIN VARIES CLEAN SAND TO MIN. 12" ABOVE TOP OF PIPE FOR HDPE PIPE. COMPACTED 3/4" CRUSHED STONE BEDDING ASTM-C33, SIZE 67 TO SPRINGLINE OF PIPE FOR RCP AND DI PIPE UNDISTURBED MATERIAL PLASTIC DRAIN PIPE (HDPE) SHALL BE ADS N-12 (CORRUGATED EXTERIOR/SMOOTH INTERIOR) OR EQUAL MEETING AASHTO M-252 AND H-20 LOADING.

> DI DRAIN PIPE SHALL BE CL. 50. RC DRAIN PIPE SHALL BE CLASS III UNLESS OTHERWISE NOTED.

TYPICAL DRAIN AND SEWER PIPE TRENCH NOT TO SCALE



HEADWALLS (MASONRY & CONCRETE)

E NEW H KENNETH

335 RRIN RRIN

B

m

LAND OF DAVID & DESTINY 138 CHESLEY HILL ROCHESTER, NH (

E - 102

SHEET 5 OF 5

YING INEERING POINT ROAD (603)332–2863

CROWN P CROWN P CROWN P 1 03825 (NOTED 27 10, 201 2018 - C

2018 - 068