GENERAL INFORMATION

FOR MORE INFORMATION ABOUT THIS SITE PLAN, CONTACT:

400 NORTH MAIN STREET, LLC 549 US HIGHWAY 1 BY-PASS PORTSMOUTH, NH 03801

APPLICANT

400 NORTH MAIN STREET, LLC 549 US HIGHWAY 1 BY-PASS PORTSMOUTH, NH 03801

PREPARED FOR

400 NORTH MAIN STREET, LLC 549 US HIGHWAY 1 BY-PASS PORTSMOUTH, NH 03801

RESOURCE LIST

PLANNING/ ZONING DEPARTMENT 31 WAKFFIFI D STREET (603) 335-1338 MARK SULLIVAN, PLANNING AND ZONING CITY MANAGER DESIGNEE

BUILDING DEPARTMENT

31 WAKEFIELD STREET ROCHESTER, NH 03867 (603) 332-3508 JIM GRANT, DIRECTOR

PUBLIC WORKS

45 OLD DOVER ROAD ROCHESTER NH 03867 (603) 332-4096 PETER NOURSE, P.E., DIRECTOR

POLICE DEPARTMENT

23 WAKEFIELD STREET ROCHESTER, NH 03867 (603) 330-7127 PAUL TOUSSAINT, CHIEF

FIRE DEPARTMENT 37 WAKEFIELD STREET ROCHESTER, NH 03867 MARK KLOSE, CHIEF

ASSOCIATED WITH

ARCHITECT TW DESIGNS, LLC 254 DRAKE HILL ROAD STRAFFORD, NH 03884 (603) 664-2181

GEOTECHNICAL ENGINEER

S.W. COLE ENGINEERING, INC. 10 CENTRE ROAD SOMERSWORTH, NH 03878 (603) 692-0088

LIGHTING DESIGN SK & ASSOCIATES, INC. 20 CARVER CIRCLE

(781) 821-1700

SOIL SCIENTIST

WHITESTONE ASSOCIATES, INC. 352 TURNPIKE ROAD, SUITE 320 SOUTHBOROUGH, MA 01772 (508) 485-0755

SURVEYOR

DOUCET SURVEY, INC. 102 KENT PLACE NEWMARKET, NH 03857 (603) 659-6560

TRAFFIC ENGINEER

TFMORAN, INC. 48 CONSTITUTION DRIVE BEDFORD, NH 03110 (603) 472-4488 JENNIFER PORTER, PE


WETLAND SCIENTIST GOVE ENVIRONMENTAL SERVICES 8 CONTINENTAL DRIVE

(603) 778-0644

PROPOSED AUTO **DEALERSHIP**

400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

JULY 9, 2019 (REVISED AUGUST 13, 2019)





Phone (603) 431-2222 Fax (603) 431-0910



INDEX OF SHEETS SHEET SHEET TITLE C-02 NOTES & LEGEND C-03 SOIL BOUNDARY PLAN C-04 SITE PREPARATION & DEMOLITION PLAN C-05 SITE LAYOUT PLAN C-06 GRADING & DRAINAGE PLAN C-07 UTILITY PLAN C-08 LANDSCAPE PLAN C-09 LANDSCAPE DETAILS C-10 EROSION CONTROL PLAN C-11 EROSION CONTROL NOTES C-12 WB-67 TRUCK MOVEMENT PLAN FIRE TRUCK MOVEMENT PLAN C-13 C-14 TO C-17 REFERENCE BY ASSOCIATED PROFESSIONALS 1 TO 2 EXISTING CONDITIONS (DOUCET SURVEY) A11 TO A13 PROPOSED FLOOR & ROOF PLANS (TW DESIGNS, INC.) PROPOSED EXTERIOR ELEVATIONS (TW DESIGNS, INC.) EXTERIOR ELEVATION RENDERING (TW DESIGNS, INC.) LIGHTING PLAN, SCHEDULES, AND SPECIFICATIONS (SK & ASSOCIATES, INC.)

PERMITS/APPROVALS						
	NUMBER	APPROVED	EXPIRES			
TOWN SITE PLAN	PENDING	PENDING	PENDING			
NHDES ALT. OF TERRAIN	PENDING	PENDING	PENDING			
NHDES SEWER	PENDING	PENDING	PENDING			

WAIVERS

THE FOLLOWING WAIVERS FROM THE CITY OF ROCHESTER'S LAND DEVELOPMENT REGULATIONS ARE BEING REQUESTED FROM THE PLANNING BOARD:

- 1. SITE PLAN CHECKLIST: EXISTING TOPOGRAPHIC FEATURES: SOIL TYPES AND BOUNDARIES 2. SITE PLAN CHECKLIST: EXISTING TOPOGRAPHIC FEATURES: SOIL TEST PIT LOCATIONS
- 3. SITE PLAN CHECKLIST: EXISTING TOPOGRAPHIC FEATURES: PERCOLATION TEST LOCATIONS
- 4. LAND DEVELOPMENT REGULATIONS ARTICLE III SECTION 10(A): NUMBER OF REQUIRED PARKING SPACES
- 5. LAND DEVELOPMENT REGULATIONS ARTICLE III SECTION 5(D)(8B): SHADE TREE PER 40 LINEAR FEET ALONG FRONT BUFFER
- 6. LAND DEVELOPMENT REGULATIONS ARTICLE III SECTION 5(E)(7): LANDSCAPE MEDIAN PER FOUR CONTINUIDUS PARKING ROWS

THESE PLANS ARE PERMIT DRAWINGS ONLY AND HAVE NOT BEEN DETAILED FOR CONSTRUCTION OR BIDDING.

APPROVED BY THE CITY OF	ROCHESTER PLANNING BOARD
DN	
BOARD MEMBER	AND
BOARD MEMBER	

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

COVER


PROPOSED AUTO DEALERSHIP 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019






Structural Engineers Traffic Engineers Land Surveyors Phone (603) 431-2222 Fox (603) 431-0910

47159.01

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.





GENERAL NOTES

- THESE PLANS ARE PERMIT DRAWINGS ONLY AND HAVE NOT BEEN DETAILED FOR
- THESE PLANS WERE PREPARED UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER. TEMORAN, INC. ASSUMES NO LIABILITY AS A RESULT OF ANY CHANGES OR NON-CONFORMANCE WITH THESE PLANS EXCEPT UPON THE WRITTEN APPROVAL OF THE ENGINEER OF RECORD.
- 3. THE SITE PLAN SHALL BE RECORDED IN THE STRAFFORD COUNTY REGISTRY OF DEEDS.
- 4. ALL IMPROVEMENTS SHOWN ON THE SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE CITY PLANNING DIRECTOR.
- 5. ALL WORK SHALL CONFORM TO THE APPLICABLE REGULATIONS AND STANDARDS OF THE CITY OF ROCHESTER, AND SHALL BE BUILT IN A WORKMANLIKE MANNER IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS. ALL WORK TO CONFORM TO CITY OF ROCHESTER DEPARTMENT OF PUBLIC WORKS STANDARD SPECIFICATIONS. ALL WORK WITHIN THE RIGHT-OF-WAY OF THE CITY AND/OR STATE SHALL COMPLY WITH APPLICABLE STANDARD COORDINATE ALL WORK WITHIN THE RIGHT-OF-WAY WITH APPLICABLE STANDARD CORDINATE ALL WORK WITHIN THE RIGHT-OF-WAY WITH APPLICABLE STANDARD CORDINATE ALL WORK WITHIN THE RIGHT-OF-WAY WITH APPROPRIATE CITY, COUNTY,
- AN ALTERATION OF TERRAIN PERMIT IS REQUIRED PER ENV—WQ 1503.02. THE SITE CONTRACTOR SHALL ENSURE THAT ALL WORK IS PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF INFIDES ENV—WQ 1500 OR AS APPLICABLE.
- 7. SEE EXISTING FEATURES PLAN FOR BENCHMARK INFORMATION, VERIFY TBM ELEVATIONS PRIOR TO CONSTRUCTION
- 8. CONTACT EASEMENT OWNERS PRIOR TO COMMENCING ANY WORK WITHIN THE EASEMENTS.
- 9. PRIOR TO COMMENCING ANY SITE WORK ALL LIMITS OF WORK SHALL BE CLEARLY MARKED
- 11. TFMORAN, INC. ASSUMES NO LIABILITY FOR WORK PERFORMED WITHOUT AN ACCEPTABLE PROGRAM OF TESTING AND INSPECTION AS APPROVED BY THE ENGINEER OF RECORD.
- 13. ALL DEMOLITION SHALL INSURE MINIMUM INTERFERENCE WITH ROADS, STREETS, WALKWAYS, AND ANY OTHER ADJACENT OPERATING FACILITIES. PRIOR WRITTEN PERMISSION FROM THE OWNER/DEVELOPER AND LOCAL PERMITTING AUTHORITY IS REQUIRED IF CLOSURE/OPSTRUCTIONS TO ROADS, STREET, WALKWAYS, AND OTHERS IS DEEMED NECESSARY, CONTRACTOR TO PROVIDE ALTERNATE ROUTES AROUND
- 14. REFER TO ARCHITECTURAL PLANS FOR LAYOUT OF BUILDING FOUNDATIONS AND CONCRETE ELEMENTS WHICH ABUT THE BUILDING SUCH AS STAIRS, SIDEWALKS, LOADING DOCK RAMPS PADS, AND COMPACTOR PADS. DO NOT USE SITE PLANS FOR LAYOUT OF FOUNDATIONS.
- 16. IF CONDITIONS AT THE SITE ARE DIFFERENT THAN SHOWN ON THE PLANS, THE ENGINEER SHALL BE NOTIFIED PRIOR TO PROCEEDING WITH THE AFFECTED WORK.
- A. BID AND PERFORM THE WORK IN ACCORDANCE WITH ALL LOCAL, STATE, AND NATIONAL CODES, SPECIFICATIONS, REGULATIONS, AND STANDARDS.
- B. NOTIFY ENGINEER IN WRITING OF ANY DISCREPANCIES OF PROPOSED LAYOUT AND/OR EXISTING FEATURES.
- C. EMPLOY A LICENSED SURVEYOR TO DETERMINE ALL LINES AND GRADES AND LAYOUT OF SITE FLEMENTS AND BUILDINGS
- D. THE CONTRACTOR SHALL BE RESPONSIBLE TO BECOME FAMILIAR WITH THE SITE AND ALL SURROUNDING CONDITIONS. THE CONTRACTOR SHALL ADVISE THE APPROPRIATE AUTHORITY OF INTENTIONS AT LEAST 48 HOURS IN ADVANCE.
- E. TAKE APPROPRIATE MEASURES TO REDUCE, TO THE FULLEST EXTENT POSSIBLE, NOISE, DUST AND UNSIGHTLY DEBRIS, CONSTRUCTION ACTIVITIES SHALL BE CARRIED OUT BETWEEN THE HOURS OF 7. AM AND 6 PM, MONDAY THROUGH FRIDAY AND 8 AM AND 6 PM ON SATURDCAY IN ACCORDANCE WITH "STANDARD OF INFRASTRUCTURE DESIGN,
- F. MAINTAIN EMERGENCY ACCESS TO ALL AREAS AFFECTED BY WORK AT ALL TIMES.
- G. IN ACCORDANCE WITH RSA 430:53 AND AGR 3800, THE CONTRACTOR SHALL NOT TRANSPORT INVASIVE SPECIES OFF THE PROPERTY, AND SHALL DISPOSE OF INVASIVE SPECIES ON—SITE IN A LEGAL MANNER.
- H. COORDINATE WITH ALL UTILITY COMPANIES AND CONTACT DIGSAFF (811 OR 888-344-7233) AT LEAST 72 HOURS PRIOR TO ANY EXCAVATION
- PROTECT NEW AND EXISTING BURIED LITHLITIES DURING INSTALLATION OF ELEMENTS, DAMAGED UTILITIES SHALL BE REPAIRED OR REPLACED AT NO ADDITIONAL COST TO THE OWNER.
- J. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MEANS AND METHODS OF CONSTRUCTION AND FOR CONDITIONS AT THE SITE. THESE PLANS, PREPARED BY TEMORAN, INC., DO NOT EXTEND TO OR INCLUDE SYSTEMS PERTAINING TO THE SAFETY OF THE CONSTRUCTION CONTRACTOR OR THEIR EMPLOYES, AGENTS, OR REPRESENTATIVES IN THE PERFORMANCE OF THE WORK. THE SEAL OF THE SURVEYOR OR ENGINEER HEREON DOES NOT EXTEND TO ANY SUCH SAFETY SYSTEMS THAT MAY NOW OR HEREAFTER BE INCORPORATED INTO THESE PLANS. THE CONSTRUCTION CONTRACTOR SHALL PREPARE OR OBTAIN THE APPROPRIATE SAFETY SYSTEMS WHICH MAY BE REQUIRED BY THE US OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) AND/OR LOCAL REGULATIONS.
- VERIFY LAYOUT OF PROPOSED BUILDING FOUNDATIONS WITH ARCHITECT AND THAT PROPOSED FOUNDATION MEETS PROPERTY LINE SETBACKS PRIOR TO COMMENCING ANY
- M. PROVIDE AN AS-BUILT PLAN AT THE COMPLETION OF THE PROJECT TO THE PLANNING DIRECTOR AND PER CITY REGULATIONS.
- N. IF ANY DEVIATIONS FROM THE APPROVED PLANS AND SPECIFICATIONS HAVE BEEN A MADE, THE SITE CONTRACTOR SHALL PROVIDE AS—BULL TO RAWNOS STAMPED BY A LICENSED SURVEYOR OR QUALIFIED ENGINEER ALONG WITH A LETTER STAMPED BY A QUALIFIED ENGINEER DESCRIBING ALL SUCH DEVIATIONS, AND BEAR ALL COSTS FOR PREPARING AND FLUIR ANY NEW PERMITS OR PERMIT AMENDMENTS THAT MAY BE
- AT COMPLETION OF CONSTRUCTION, THE SITE CONTRACTOR SHALL PROVIDE A LETTER CERTIFYING THAT THE PROJECT WAS COMPLETED IN ACCORDANCE WITH THE APPROVED PLANS AND SPECIFICATIONS, AND A LETTER STAMPED BY A OULDIFIED ENGINEER THAT THEY HAVE OBSERVED ALL UNDERGROUND DETENTION SYSTEMS, INFILTRATION SYSTEMS FOR FILTERING SYSTEMS PRIOR TO BACKFILL, AND THAT SUCH SYSTEMS CONFORM TO THE APPROVED PLANS AND SPECIFICATIONS.

GRADING NOTES

- THE CONTRACTOR SHALL ENSURE THAT ALL WORK IS PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF NHDES ENV-WQ 1500 AS APPLICABLE.
- THE CONTRACTOR SHALL PREPARE, MAINTAIN, AND EXECUTE A S.W.P.P.P. IN ACCORDANCE WITH EPA REGULATIONS AND THE CONSTRUCTION GENERAL PERMIT.

- 4. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CHECK THE ACCURACY OF THE TOPOGRAPHY AND REPORT ANY DISCREPANCIES TO THE ENGINEER PRIOR TO ANY EARTHWORK BEIND FERFORMED ON THE SITE, NO CLAIM FOR EXTRA WORK WILL BE CONSIDERED FOR PAYMENT AFTER EARTHWORK HAS COMMENCED.
- THE CONTRACTOR SHALL REFER TO THE GEOTECHNICAL REPORT FOR INFORMATION ABOU SOIL AND GROUNDWATER CONDITIONS. THE CONTRACTOR SHALL FOLLOW THE GEOTECHNIC ENGINEERS RECOMMENDED METHODS TO ADDRESS ANY SOIL AND GROUNDWATER ISSUES THAT ARE FOUND ON SITE.
- COORDINATE WITH GEOTECHNICAL/STRUCTURAL PLANS FOR SITE PREPARATION AND OTHER RUILDING INFORMATION
- COORDINATE WITH ARCHITECTURAL PLANS FOR DETAILED GRADING AT BUILDING, AND SIZE AND LOCATION OF ALL BUILDING SERVICES.
- 8. COORDINATE WITH MECHANICAL AND PLUMBING PLANS FOR ROOF DRAIN INFORMATION,
- WORK TO PROVIDE SMOOTH TRANSITIONS. THIS INCLUDES GRADING, PAVEMENT, CURBING, SIDEWALKS, AND ALIGNMENTS.
- 10. THE CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE BUILDING ENTRANCE, RAMPS AND LOADING
- 11. THE SITE SHALL BE GRADED SO ALL FINISHED PAVEMENT HAS POSITIVE DRAINAGE AND SHALL NOT POND WATER DEEPER THAN ½ INCH FOR A PERIOD OF MORE THEN 15 MINUTES AFTER FLOODING.
- 12. ALL ELEVATIONS SHOWN AT CURB ARE TO THE BOTTOM OF CURB UNLESS OTHERWISE NOTED. CURBS HAVE A 6" REVEAL UNLESS OTHERWISE NOTED.
- 13. ALL SIDEWALK AND OTHER CURB REVEALS SHALL BE 6" WITH A TOLFRANCE OF PLUS OF MINUS 3/8". WHERE SIDEWALK IS TO BE FLUSH, THE PAVEMENT REVEAL SHALL BE 1/4" WITH A TOLERANCE OF 1/8".
- 14. THE FINISHED GRADE AT BOTTOM OF ALL ACCESSIBLE RAMPS SHALL BE FLUSH WITH PAVEMENT WITH A TOLERANCE OF PLUS OR MINUS 1/4".
- 15. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE PRIOR TO INSTALLATION OF FINISHED PAVEMENT.
- 16. ROAD AND DRAINAGE CONSTRUCTION SHALL CONFORM TO THE TYPICAL SECTIONS AND DETAILS SHOWN ON THE PLANS AND SHALL MEET LOCAL STANDARDS AND THE REQUIREMENTS OF THE LATEST NHOOT STANDARD SPECIFICATIONS FOR ROADS AND BRIDGE CONSTRUCTION AND THE NHOOT STANDARD STRUCTURE DRAWINGS UNLESS OTHERWISE
- 17. STORMWATER DRAINAGE SYSTEM SHALL BE CONSTRUCTED TO LINE AND GRADE AS SHOWN ON THE PLANS. CONSTRUCTION METHODS SHALL CONFORM TO NHOOT STANDARD SPECIFICATIONS, SECTION 603. CATCH BASINS AND DRAIN MANHOLES SHALL CONFORM TO SECTION 604. ALL CATCH BASIN GRATES SHALL BE TYPE B AND CONFORM TO NHOOT STANDARDS AND SPECIFICATIONS UNLESS OTHERWISE NOTED.
- 18. NO FILL SHALL BE PLACED IN ANY WETLAND AREA
- ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED, FERTILIZER AND MULCH.

MINIMUM DENSITY

BELOW PAVED OR CONCRETE AREAS

TRENCH BEDDING MATERIAL AND SAND BLANKET BACKFILL BELOW LOAM AND SEED AREAS SELUM LOAM AND SELD AREAS
*ALL PERCENTAGES OF COMPACTION SHALL BE OF THE MAXIMUM DRY DENSITY AT THE
OPTIMUM MOISTURE CONTENT AS DETERMINED AND CONTROLLED IN ACCORDANCE WITH
ASTM D-1557, METHOD C. FIELD DENSITY TESTS SHALL BE MADE IN ACCORDANCE WITH
ASTM D-1556 OR ASTM D-6938.

CONSTRUCTION SEQUENCE NOTES (FOR ALTERATION OF TERRAIN)

- 1. DO NOT DISCHARGE SEDIMENT-LADEN WATERS FROM CONSTRUCTION ACTIVITIES (RUNOFF, WATER FROM EXCAVATIONS) TO THE INFILTRATION BASINS.
- AFTER THE BASIN IS EXCAVATED TO THE FINAL DESIGN ELEVATION, THE FLOOR SHOULD BE DEEPLY TILLED WITH A ROTARY TILLER OR DISC HARROW TO RESTORE INFILTRATION RATES, FOLLOWED BY A PASS WITH A LEVELING DRAG.
- DO NOT PLACE INFILTRATION SYSTEMS INTO SERVICE UNTIL THE CONTRIBUTING AREAS HAVE BEEN FULLY STABILIZED.

UTILITY NOTES

- LENGTH OF PIPE IS FOR CONVENIENCE ONLY. ACTUAL PIPE LENGTH SHALL BE DETERMINED IN THE FIELD.
- ALL PROPOSED UTILITY WORK, INCLUDING MATERIAL, INSTALLATION, TERMINATION, EXCAVATION, BEDDING, BACKFILL, COMPACTION, TESTING, CONNECTIONS, AND CONSTRUCTION SHALL BE COORDINATED WITH AND COMPLETED IN ACCORDANCE WITH THE APPROPRIATE REQUIREMENTS, CODES, AND STANDARDS OF ALL CORRESPONDING UTILITY ENTITIES AND SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION, SIZE, AND ELEVATION OF ALL EXISTING UTILITIES, SHOWN OR NOT SHOWN ON THESE PLANS, PRIOR TO THE START OF ANY CONSTRUCTION. THE ENGINEER SHALL BE NOTHIED IN WRITING OF ANY UTILITIES FOR ANY CONSTRUCTION AND APPROPRIATE REMEDIAL ACTION BE AGREED TO BY THE ENGINEER BEFORE, PROCEEDING WITH THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT "DIGSAFE" (811) AT LEAST 72 HOURS BEFORE DIGGING.
- COORDINATE ALL WORK ADJACENT TO PROPOSED BUILDINGS WITH ARCHITECTURAL BUILDING DRAWNGS. CONFIRM UTILITY PENETRATIONS AND INVERT ELEVATIONS ARE COORDINATED PRIOR TO INSTALLATION.
- THE CONTRACTOR SHALL CONTACT ALL UTILITY COMPANIES OWNING UTILITIES, EITHER OVERHEAD OR UNDERGROUND, WITHIN THE CONSTRUCTION AREA AND SHALL COORDINATE AS NECESSARY WITH THE UTILITY COMPANIES OF SAID UTILITIES. THE PROTECTION OR RELOCATION OF UTILITIES IS ULTIMATELY THE RESPONSIBILITY OF THE CONTRACTOR.
- 6. THE EXACT LOCATION OF NEW UTILITY CONNECTIONS SHALL BE DETERMINED BY THE CONTRACTOR IN COORDINATION WITH UTILITY COMPANY, COUNTY AGENCY, AND/OR PRIVATE UTILITY COMPANY.
- THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES, AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER THE UTILITY INSTALLATION COMPLETE AND OPERATIONAL.
- ALL UTILITY COMPANIES REQUIRE INDIVIDUAL CONDUITS. CONTRACTOR TO COORDINATE WITH TELEPHONE, CABIE, AND ELECTRIC COMPANIES REGARDING NUMBER, SIZE, AND TYPE OF CONDUITS REQUIRED PRIOR TO INSTALLATION OF ANY CONDUIT.
- 9. SANITARY SEWER SHALL BE CONSTRUCTED TO THE STANDARDS AND SPECIFICATIONS AS SHOWN ON THESE PLANS. ALL SEWER MAINS AND FITTINGS SHALL BE PVC AND SHALL CONFORM TO ASTM F 679 (SDR 35 MININUM), ALL SEWER CONSTRUCTION SHALL BE IN ACCORDANCE WITH NH CODE OF ADMINISTRATIVE RULES ENV-MO 700, SANITARY MANHOLES SHALL CONFORM TO NHOES WATER DIVISION WASTEWATER ENGINEERING BUREAU STANDARDS AND SPECIFICATIONS SHOWN HEREON.
- 10. ON—SITE WATER DISTRIBUTION SHALL BE TO CITY OF ROCHESTER STANDARDS AND SPECIFICATIONS. WATER MAINS SHALL HAVE A MINIMUM OF 5.5 FEET COVER. WHERE WATER PIPES CROSS SEWER LINES A MINIMUM OF 18" VERTICAL SEPARATION BETWEEN THE TWO OUTSIDE PIPE WALLS SHALL BE OBSERVED. HORIZONTAL SEPARATION BETWEEN WATER AND SEWER SHALL BE 10 FEET MINIMUM. WHERE A SANITARY LINE CROSSES A WATER LINE, ENCASE THE SANITARY LINE IN 6" THICK CONCERTE FOR A DISTANCE OF 10" EITHER SIDE OF THE CROSSING, OR SUBSTITUTE RUBBER—CASKETED PRESSURE PIPE FOR THE SAME DISTANCE. WHEN SANITARY LINES PASS BELOW WATER LINES, LAY PIPE SO THAT NO JOINT IN THE SANITARY LINE WILL BE CLOSER THAN 3" HORIZONTALLY TO THE WATER LINE.
- THRUST BLOCKS SHALL BE PROVIDED AT ALL LOCATIONS WHERE WATER LINE CHANGES DIRECTIONS OR CONNECTS TO ANOTHER WATER LINE,
- 12. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR CONDUIT AND WIRING TO ALL SIGNS AND LIGHTS. CONDUIT TO BE A MINIMUM OF 24" BELOW FINISH GRADE.
- 13. ALL PROPOSED UTILITIES SHALL BE UNDERGROUND. ALL UNDERGROUND CONDUITS SHALL
- 15. PROVIDE PERMANENT PAVEMENT REPAIR FOR ALL UTILITY TRENCHES IN EXISTING ROAD OR PAVEMENT IN TERMAIN. SAW CUIT TRENCH, PAVEMENT AND GRANULAR BASE THICKNESS TO MATCH EXISTING PAVEMENT. OBTAIN ALL PERMITS REQUIRED FOR TRENCHING.
- 16. UNLESS OTHERWISE SPECIFIED, ALL UNDERGROUND STRUCTURES, PIPES, CHAMBERS, ETC. SHALL BE COVERED WITH A MINIMUM OF 18" OF COMPACTED SOIL BEFORE EXPOSI-VEHICLE LOADS.
- 17. THE PROPERTY WILL BE SERVICED BY THE FOLLOWING: DRAINAGE PRIVATE SEWER MUNICIPAL WATER MUNICIPAL

UNITIL

EVERSOURCE

CONSOLIDATED COMMUNICATIONS FKA FAIRPOINT COMMUNICATIONS

ATLANTIC BROADBAND

APPROVED BY THE CITY OF ROCHESTER PLANNING BOARD AND

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2


NOTES & LEGEND

PROPOSED AUTO DEALERSHIP **400 NORTH MAIN STREET** ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019



No.15699

CENSED

8/13/2010

Structural Engineers Traffic Engineers Land Surveyors Scientists

170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

C-02

ELEVATION

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

EDGE OF PAVEMENT

This plan is not effective unless signed by a duly authorized officer o Thomas F. Moron, Inc.

ON CENTER

PERFORATED

TOP OF WALL

UNDERGROUND


ACCESSIBLE WHEELCHAIR RAMP


HEADWALL


LIGHT POLE
OUTLET CONTROL STRUCTURE
OIL WATER SEPARATOR
POLYVANYL, CHLORIDE PIPE
REINFORCED CONCRETE PIPE
ROOF DRAIN
SEWER MANHOLE
TAPPING SLEEVE, VALVE, AND BOX
UTILITY POLE


TYPICAL


1 8/13/19 TRG COMMENTS REV. DATE DESCRIPTION














*WAIVER NEEDED, ARTICLE III SEC. 5(D)(8f)

CONTACT DIG SAFE 72 BUSINESS HOURS PRIOR TO CONSTRUCTION

this plan is not effective unless signed by a duly authorized officer of thomas F. Moran, Inc.

LANDSCAPE LEGEND QTY BOTANICAL NAME COMMON NAME SYMBOL SIZE REMARKS 3" TO 3 1/2" B&B ACER SACCHARUM 'GREEN MOUNTAIN' GREEN MOUNTAIN SUGAR MAPLE 3" TO 3 1/2" B&B (.) 3" TO 3 1/2" B&B 2' TO 2 1/2" B&B OXYDENDRUM ARBOREUM SOURWOOD 2' TO 2 1/2" CAL. B&B * 7' TO 8' B&B PLATANUS ACREIFOLIA 'BLOODGOOD BLOODGOOD LONDON PLANETREE 3" TO 3 1/2" CAL. B&B 8 PLATANUS ACREIFOLIA 'EXCLAMATION'
EXCLAMATION PLANETREE 3" TO 3 1/2" 3" TO 3 1/2" CAL. 3" TO 3 1/2" CAL. B&B AZALEA 'PLEASANT WHITE'
PLEASANT WHITE AZALEA 7 GAL CONT. 0 3 GAL. CONT. 3 GAL. 0 HYDRANGE PANICULATA 'BOMBSHELL' BOMBSHELL PANICLE HYDRANGEA 8 7 GAL. CONT PHYSOCARPUS OPULIFOLIUS 'COPPERTINA' COPPERTINA NINEBARK 0 2' TO 2 1/2' B&B TAXUS M. 'GREENWAVE' GREENWAVE YEW 0 5 GAL. CONT CHAMAECYPARIS PISIFERA 'FILIFERA MOPS' MOPS THREAD-LEAF FALSECYPRESS 5 GAL CONT. 7 GAL JUNIPERUS CHINENSIS 'SARGENTII' GREEN SERGEANT JUNIPER 18" TO 24" B&B 18" TO 24" B&B THUJA O. 'TECHNY'
MISSION ARBORVITAE PENNISETUM ALOPECUROIDES 'HAMELN' HAMELN FOUNTAIN GRASS 7 GAL. CONT. 20 HELICTOTRICHON S. 'SAPPHIRE' SAPPHIRE OAT GRASS 2 GAL. CONT

SEE DETAIL SHEET FOR LANDSCAPE NOTES

APPROVED BY THE CITY OF ROCHESTER PLANNING BOARD BOARD MEMBER __

LANDSCAPE PLAN

400 NORTH MAIN STREET

SCALE:1' - 40'(22X34)

JULY 9, 2019



1 8/13/19 TRG COMMENTS

REV. DATE



Civil Engineers Structural Engineers Traffic Engineers Land Surveyors

Portsmouth, NH 03801 Phone (603) 431-2222 Landscape Architects Fax (603) 431-0910

47159.01

C-08

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

PROPOSED AUTO DEALERSHIP ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR 400 NORTH MAIN STREET, LLC

1' = 80'(11X17)

WATER THOROUGHLY TWICE WITHIN THE FIRST 48 HOURS. NEVER CUT A LEADER ... (ITEM II)
FOR TREES 5" IN HEIGHT OR GREATER
(3) \$12 GA. GALV. TWISTED WIRES AT 120'
SPACING WITH 6 1/2" GAL TURNBUCKLE
WIRE IN RUBBER HOSE AGOUND TREE
ATTACH TO TREE AT 1/2 TO 2/3 HEIGHT
OF TREE ADOVE GRADE
ANCHOR WITH 2"X2X2" SPRUCE STAKE
ANCHOR WITH 2"X2X2" SPRUCE STAKE (ITEM I)
FOR TREES LESS THAN 5' IN HEIGHT
(3) 2"x2"x5" SPRUCE STAKES AT 120'
— SPACING, A MINIMUM OF 36" IN GROUND.
STAKES TO BE CLEAR OF ROOTBALL ANCHOR WITH 2"x2x2" SPRUCE STAKE BURIED BELOW GRADE CLEAR OF ROOTBALL 3 INCH SHREDDED MULCH. DO NOT PLACE MULCH IN CONTACT WITH TREE TRUNK. FILTER FABRIC FOR WEED CONTROL UNDER BARK MULCH. (KEEP OUT OF DEPRESSION) REMOVE ALL TWINE, ROPE, WIRE,

AND BURLAP FROM TOP HALF OF
ROOT BALL, IF PLANT IS SHIPPED
WITH A WIRE BASKET AROUND THE
ROOT BALL, CUT THE WIRE BASKET
IN FOUR PLACES AND FOLD DOWN 16 MIN 3 INCH HIGH EARTH SAUCER BEYOND EDGE OF ROOT BALL. - SET TOP OF ROOT BALL FLUSH TO GRADE OR PLANTING MIXTURE: 20 PARTS – TOPSOIL, 4 PARTS PEAT MOSS AND ONE PART WELL ROTTED MANURE OR OTHER COMPOSTED ORGANIC MATTER OF LOW PH. BACKFILL IN LOOSE LIFTS OF (1-2 IN.) HIGHER IN SLOWLY DRAINING SOILS.

EVERGREEN PLANTING

NOT TO SCALE

CUT AND REMOVE BURLAP FROM—
TOP 2/3 OF ROOTBALL, REMOVE
ALL STRING, FOLD REMAINING
BURLAP DOWN INTO PLANT PIT. IF
BURLAP IS SYNTHETIC, REMOVE
COMPLETELY, WHEN PLANTING
CONTAINER GROWN PLANTS,
REMOVE THE BALL FROM THE
CONTAINER AND LOSSEN THE
OUTSIDE LAYER OF THE ROOT
SYSTEM BY SCORDING WITH A CONTAINER GROWN PLANTS,
REMOVE THE BALL FROM THE
CONTAINER AND LOOSEN THE
OUTSIDE LAYER OF THE ROOT
SYSTEM BY SCORING WITH A
CLEAN KNIFE, DIVIDE ALL CIRCLING
DIMMETER OF HOLE SHALL—
BE TWICE THE DIAMETER OF -3" SHREDDED BARK MULCH - FILTER FABRIC FOR WEED 3 INCH HIGH EARTH SAUCER BEYOND EDGE OF ROOT BALL. PLANTING MIXTURE: 20 PARTS — TOPSOIL, 4 PARTS PEAT MOSS AND ONE PART WELL ROTTED MANURE OR OTHER COMPOSTED ORGANIC MATTER OF LOW PH. BACKFILL IN LOOSE LIFTS OF 6"-9" DEPTH. LIGHTLY TAMP -SET TOP OF ROOT BALL FLUSH TO GRADE OR (1-2 IN.) HIGHER IN SLOWLY DRAINING SOILS.

SHRUB PLANTING

NOT TO SCALE

LANDSCAPE NOTES

- CONTRACTOR WILL LOCATE, VERIFY AND MARK ALL EXISTING AND NEWLY INSTALLED UNDERGROUND UTILITIES PRIOR TO ANY LAWNWORK OR PLANTING.
 ANY CONFLICTS WHICH MIGHT OCCUR BETWEEN PLANTING AND UTILITIES WILL IMMEDIATELY BE REPORTED TO THE LANDSCAPE ARCHITECT OR OWNERS
 REPRESENTATIVE, SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
- CONTRACTOR WILL FURNISH AND PLANT ALL PLANTS IN QUANTITIES AS SHOWN ON THIS PLAN. IN CASES OF DISCREPANCY BETWEEN PLAN AND LIST CLARIFY WITH LANDSCAPE ARCHITECT PRIOR TO PLACING PURCHASE ORDER AND AGAIN PRIOR TO PLANTING.
- 3. SEE PLANTING DETAILS AND IF INCLUDED, SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- 4. NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT PRIOR WRITTEN APPROVAL OF THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO MAKE THE APPROPRIATE ARRANGEMENTS TO PROVIDE ALL PLANTS AND MATERIALS TO ACCOMMODATE PLANTING WITHIN THE TIME ALLOWED BY THE CONSTRUCTION SCHEDULE.
- 6. PLANTING SHALL BE COMPLETED FROM APRIL 15TH THROUGH OCTOBER 15TH UNLESS OTHERWISE NOTED IN SPECIFICATIONS. THERE WILL BE NO PLANTING DURING JULY AND AUGUST UNLESS SPECIAL PROVISIONS ARE MADE FOR DROUGHT BY PROVIDING ADDITIONAL WATERING.
- PLANTS WILL BE IN ACCORDANCE, AT A MINIMUM, WITH CURRENT EDITION OF "AMERICAN STANDARDS FOR NURSERY STOCK" AS PUBLISHED BY THE AMERICAN HORTICULTURE INDUSTRY ASSOCIATION.
- 9. TREES WILL BE PRUNED IN ACCORDANCE WITH THE LATEST EDITION OF ANSI A300 PART 1, "TREE, SHRUB AND OTHER WOODY PLANT MAINTENANCE
- 10. PLANTS MATERIAL IS SUBJECT TO APPROVAL / REJECTION BY THE LANDSCAPE ARCHITECT AT THE SITE AND AT THE NURSERY,
- 12. NEWLY PLANTED MATERIAL WILL BEAR THE SAME RELATIONSHIP TO FINISHED GRADE AS TO THE ORIGINAL GRADE OF THE PLANT PRIOR TO DIGGING.

- 15. PLANT MATERIAL WILL BE LOCATED OUTSIDE BUILDING DRIPLINES AND ROOF VALLEY POINTS OF CONCENTRATION TO PREVENT DAMAGE TO PLANTS. CLARIFY DISCREPANCIES WITH LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- 16. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED, WILL RECEIVE SIX (6) INCH LOAM AND SEED AT THE DIRECTION OF THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE.
- 17. TREE STAKES AND WRAP WILL REMAIN IN PLACE FOR NO LESS THAN 6 MONTHS AND NO MORE THAN 1 YEAR, CONTRACTOR WILL REMOVE,
- 18. ALL PLANT GROUPINGS WILL BE IN MULCH BEDS UNLESS OTHERWISE SPECIFIED OR NOTED ON PLANS. WHERE MULCHED PLANT BED ABUTS LAWN, PROVIDE TURF CUT EDGE.
- 19. ALL PLANT BEDS WILL INTERSECT WITH PAVEMENT AT 90 DEGREES UNLESS OTHERWISE NOTED ON PLANS.
- 20. ALL PLANT BED EDGES WILL BE SMOOTH AND CONSISTENT IN LAYOUT OF RADII AND TANGENTS. IRREGULAR, WAVY EDGES WILL NOT BE ACCEPTED.

LANDSCAPE GUARANTEE AND MAINTENANCE NOTES

- 1. CONTRACTOR WILL BE RESPONSIBLE FOR ALL MEANS, METHODS AND TECHNIQUES OF WATERING,
- CONTRACTOR WILL BEGIN WATERING IMMEDIATELY AFTER PLANTING. ALL PLANTS WILL BE THOROUGHLY WATERED TWICE DURING THE FIRST 48 HOUR PERIOD AFTER PLANTING. ALL PLANTS WILL BE WATERED WEEKLY, OR MORE OFTEN, IF NECESSARY DURING THE FIRST GROWING SEASON BUT NOT LESS THAN ONE YEAR.
- 3. WATER ALL LAWNS AS REQUIRED. DO NOT LET NEWLY PLANTED LAWNS DRY OUT DURING THE FIRST FOUR WEEKS MINIMUM.
- 4. ALL NEW LAWNS WILL BE MAINTAINED AND MOWED A MINIMUM THREE (3) TIMES BEFORE REQUESTING REVIEW BY LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE FOR ACCEPTANCE. MAINTENANCE AND MOWING WILL CONTINUE UNTIL ACCEPTED BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE IS ISSUED IN WRITING.
- 5. THE CONTRACTOR WILL MAINTAIN AND GUARANTEE ALL PLANTINGS TO BE IN GOOD HEALTHY, FLOURISHING AND ACCEPTABLE CONDITION FOR A PERIOD OF ONE (1) YEAR BEGINNING AT THE DATE OF ACCEPTANCE BY THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE. ALL GRASSES, TREES AND SHRUBS THAT, IN THE OPINION OF THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATE SHOWING LESS THAN BOX HEALTHY GROWN AT THE END OF ONE (1) YEAR PERIOD WILL BE IMMEDIATELY REPLACED BY THE CONTRACTOR
- 6. ALL ORNAMENTAL GRASSES WILL BE CUT BACK EVERY FALL OR EARLY SPRING.

6" LOAM (ITEM 641)

MULCH (ITEM 645.111)

LOAM & SEED

SEED (ITEM 644) LIMESTONE (ITEM 642) FERTILIZER (ITEM 643.11)

NOT TO SCALE

- 7. DECIDIOUS PLANT MATERIAL INSTALLED AFTER SEPTEMBER 30 AND BEFORE APRIL 15 WILL NOT BE REVIEWED THAT SEASON FOR ACCEPTANCE DUE TO STAGE OF LEAF PHYSIOLOGY. THIS PLANT MATERIAL WILL NOT BE REVIEWED UNTIL FOLLOWING GROWING SEASON. GUARANTEE PERIOD WILL BEGIN ONLY AFTER ACCEPTANCE BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE.
- B. EVERGREEN PLANT MATERIAL INSTALLED AFTER OCTOBER 30 AND BEFORE APRIL 15 WILL NOT BE REVIEWED THAT SEASON FOR ACCEPTANCE DUE TO ENC OF GROWTH SEASON. THIS PLANT MATERIAL WILL NOT BE REVIEWED UNTIL FOLLOWING GROWING SEASON. GUARANTEE PERIOD WILL BEGIN ONLY AFTER ACCEPTANCE BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE.

HYDROSEEDING NOTES

HYDROSEEDING MAY BE USED AS AN ALTERNATE METHOD OF SEEDING. THE APPLICATION OF LIMESTONE AS NECESSARY, FERTILIZER AND GRASS SEED MAY BE ACCOMPLISHED IN ONE OPERATION BY THE USE OF A SPRAYING MACHINE APPROVED BY THE LANDSCAPE ARCHITECT OR CIVIL ENGINEER. THE MATERIALS SHALL BE MIXED WITH WATER IN THE MACHINE AND SHALL CONFORM TO RELATIVE REQUIREMENTS OF SECTION 644 OF NH. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.

INVASIVE PLANT NOTES

1. EXISTING NON-NATIVE, INVASIVE PLANT SPECIES WILL BE IDENTIFIED, REMOVED, DESTROYED AND LEGALLY DISPOSED OF IN ACCORDANCE WITH THE LATEST UNIVERSITY OF NEW HAMPSHIRE CODERATIVE EXTENSION METHODS OF DISPOSING NON-NATIVE INVASIVE PLANTS. SEE "MANAGE AND CONTROL INVASIVES" AND PROPERTY DISPOSE OF INVASINE PLANTS.

PRICING & CONSTRUCTION DOCUMENT NOTES

- 1. CONTRACTOR WILL PRICE PLANT MATERIAL IN QUANTITIES SUFFICIENT TO COMPLETE PLANTINGS GRAPHICALLY SHOWN ON THESE DRAWINGS OR IN PLANT LIST, WHICHEVER IS GREATER. IN CASES OF DISCREPANCY BETWEEN PLAN AND LIST CLARIFY WITH LANDSCAPE ARCHITECT PRIOR TO PLACING PURCHASE ORDER AND AGAIN PRIOR TO PLANTING.
- CONTRACTOR WILL VERIFY PRIOR TO PRICING IF SITE SOILS ARE VERY POORLY DRAINING OR IF LEDGE IS PRESENT. IF CONTRACTOR ENCOUNTERS VERY
 POORLY DRAINING SOILS (BATH TUB EFFECT) OR LEDGE THAT IMPACTS PROPOSED PLANTING PLAN, NOTIFY LANDSCAPE ARCHITECT OR OWNERS'
 REPRESENTATIVE FOR DIRECTION PRIOR TO PRICING AND AGAIN PRIOR TO PERFORMING ANY WORK.
- PARKING AREA PLANTED ISLANDS WILL HAVE MINIMUM OF 1'-0" TOPSOIL PLACED TO THE TOP OF CURB ELEVATION. REMOVE ALL CONSTRUCTION DEBRIS
 BEFORE PLACING TOPSOIL.
- 4. EXISTING TREES SHOWN ON THE PLAN WILL REMAIN UNDISTURBED. ALL EXISTING TREES SHOWN TO REMAIN WILL BE PROTECTED WITH A 4-FOOT SNOW FENCE PLACED AT THE DRIP LINE OF THE BRANCHES OR AT 8 FEET MINIMUM FROM THE TREE TRUNK.
- 5. CONTRACTOR WILL STAKE OR PLACE ON GROUND ALL PROPOSED PLANT MATERIALS PER PLAN. CONTACT LANDSCAPE ARCHITECT FOR REVIEW AND APPROVAL PRIOR TO INSTALLATION.
- COORDINATE WITH LANDSCAPE ARCHITECT'S CONTRACTED NUMBER OF SITE VISITS WHEN PLANNING FOR INSPECTION. NOTIFY LANDSCAPE ARCHITECT 72
 HOURS MINIMUM IN ADVANCE OF REQUESTED SITE VISIT.

SEEDING NOTES

- 1. SEEDING SHALL BE DONE BETWEEN APRIL 1 TO JUNE 15 OR AUGUST 15 TO OCTOBER 15, EXCEPT FOR RESEEDING OF BARE SPOTS AND MAINTENANCE. ALL DISTURBED AREAS NOT COVERED BY BUILDINGS, PAVING OR AREAS THAT HAVE NOT BEEN OTHERWISE DEVELOPED SHALL BE SEEDED OR SODDED. SLOPES GREATER THAN 3:1 SHAL BE PROTECTED WITH AN EROSION CONTROL BLANKET. AFTER OCTOBER 15 DISTURBED SOILS SHALL BE PROTECTED IN ACCORDANCE WITH THE WINTER CONSTRUCTION MATES.
- 2. SLOPES UP TO AND INCLUDING 3:1 GRADE, SEED WILL BE NEW ENGLAND EROSION CONTROL & RESTORATION MIX PER NEW ENGLAND WETLANDS PLANTS INC., AWHERST, MA.
- SLOPES STEEPER THAN 3:1 GRADE, SEED WILL BE NEW ENGLAND EROSION CONTROL & RESTORATION MIX PER NEW ENGLAND WETLANDS PLANTS INC., AMHERST, MA. SEE CIVIL FOR ADDITIONAL EROSION CONTROL MEASURES.
- 4. GENERAL SEED WILL BE NHDOT SPECIFICATION SECTION 644, TABLE 644-1-PARK SEED TYPE 15, INCLUDING NOTES TO TABLE 1, 2 & 3.

IRRIGATION NOTES

- 1. THE IRRIGATION SYSTEM SHALL BE DESIGNED BY AN APPROVED IRRIGATION DESIGN/BUILD CONTRACTOR OR BY AN APPROVED EQUAL, TO BE DETERMINED BY THE OWNERS
- 2. THE CONTRACTOR IS RESPONSIBLE FOR SUBMITTING THE IRRIGATION SYSTEM DESIGN AND SHOP DRAWINGS TO THE OWNER 30 DAYS PRIOR TO THE START OF CONSTRUCTION
- 3. THE CONTRACTOR SHALL VERIFY LOCATIONS OF ALL EXISTING AND PROPOSED UTILITIES AND NOTIFY THE OWNER'S REPRESENTATIVE OF CONFLICTS.
- 4. THE IRRIGATION CONTRACTOR IS RESPONSIBLE FOR, BUT NOT LIMITED TO, THE COMPLETE INSTALLATION OF THE IRRIGATION SYSTEM AND SHALL FOLLOW ALL APPLICABLE
- 5. REFER TO ARCHITECTURAL PLANS FOR LOCATION OF THE IRRIGATION SYSTEM'S BUILDING CONNECTION, 6. REFER TO MANUFACTURER'S INSTRUCTIONS AND PRODUCT SPECIFICATIONS FOR INSTALLATION



BOARD MEMBER BOARD MEMBER

APPROVED BY THE CITY OF ROCHESTER PLANNING BOARD

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

LANDSCAPE DETAILS

PROPOSED AUTO DEALERSHIP **400 NORTH MAIN STREET** ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

SCALE, AS SHOWN

JULY 9, 2019





Structural Engineers Traffic Engineers Land Surveyors MSC Scientists

Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com


CK MSK CADFILE 47159-01_Landscape.dwg

C-09

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

All rights reserved. These plans and materials may not be copied, olicated, replicated or otherwise reproduced in any form whatsoeve tout the prior written permission of Thomas F. Moran, Inc. his plan is not effective unless signed by a duly authorized officer





NOTES

- 1. SEE GENERAL EROSION CONTROL NOTES ON THE EROSION CONTROL DETAIL SHEET
- INSTALL SILT BARRIER ALONG THE PERIMETER OF THE AREA TO BE DISTURBED AS FIRST ORDER OF WORK.
- 3. PROVIDE INLET PROTECTION BARRIERS AROUND ALL EXISTING AND PROPOSED STORM DRAINAGE INLETS WITHIN THE WORK LIMITS AND MAINTAIN FOR THE DURATION OF THE PROJECT UNTIL PAYEMENT HAS BEEN INSTALLED. INLET PROTECTION BARRIERS SHALL BE IN PLACE AT ALL CATCH BASINS PRIOR TO THE DISTURBANCE OF SOIL.
- 4. DUST CONTROL SHALL BE MAINTAINED THROUGHOUT THE CONSTRUCTION PERIOD. IT SHALL BE ACCOMPLISHED BY THE UNIFORM APPLICATION OF CALCIUM CHLORIDE AT THE RATE OF 1-1/2 POUNDS PER SQUARE YARD BY MEANS OF A LIME SPREADER OR OTHER APPROVED METHOD. WATER MAY ALSO BE USED FOR DUST CONTROL, AND APPLIED BY SPRINKLING WITH WATER TRUCK DISTRIBUTIORS, AS REQUIRED.
- 5. THE SITE WILL REQUIRED.

 5. THE SITE WILL REQUIRE A USEPA NPDES PERMIT FOR STORMWATER DISCHARGE FOR THE SITE CONSTRUCTION SINCE THE DISTURBANCE EXCEEDS ONE ACRE, THE CONSTRUCTION SITE OPERATOR SHALL DEVELOP AND IMPLEMENT A CONSTRUCTION STORM WATER POLLUTION PREVENTION PLAN (SWPPP) IN ACCORDANCE WITH EPA REGULATIONS AND THE CONSTRUCTION GENERAL PERMIT WHICH SHALL REMAIN ON SITE AAND MADE ACCESSIBLE TO THE PUBLIC, THE SITE CONTRACTOR SHALL COORDINATE WITH THE OWNER TO SUBMIT AN ENOI AT LEAST 14 DAYS IN ADVANCE OF ANY EARTHWORK ACTIVITIES AT THE SITE. A COMPLETED NOTICE OF TERMINATION (NOT) SHALL BE SUBMITTED TO NPDES PERMITTING AUTHORITY WITHIN 30 DAYS AFTER EITHER OF THE FOLLOWING CONDITIONS HAVE BEEN METE: FINAL STABILIZATION HAS BEEN ACHIEVED ON ALL PORTIONS OF THE SITE FOR WHICH THE PERMITTEE IS RESPONSIBLE FOR, OR ANOTHER OPERATOR /PERMITTEE HAS ASSUMED CONTROL OVER ALL AREAS OF THE SITE THAT HAVE NOT BEEN FINALLY STABILIZED.
- 6. SILT PROTECTION MEASURES SHALL BE INSTALLED IN ACCORDANCE WITH THE DETAILS CONTAINED IN THIS PLAN SET.
- CONSTRUCT JUTE MATTING ON ALL SLOPES STEEPER THAN 3:1, DISTURBED AREAS SLOPING TOWARDS WETLANDS AND ALL LOCATIONS SHOWN ON PLAN.
- INSPECT EROSION CONTROL MEASURES WEEKLY AND AFTER EACH RAIN STORM OF 0.10 INCH OR GREATER. REPAIR/MODIFY SILT BARRIER AS NECESSARY TO MAXIMIZE FILTER EFFICIENCY. REMOVE SEDIMENT WHEN SEDIMENT IS 1/3 THE STRUCTURE HEIGHT.
- PROVIDE SILT BARRIERS AT THE BASE OF CUT AND FILL SLOPES UNTIL COMPLETION OF THE PROJECT OR UNTIL VEGETATION BECOMES ESTABLISHED ON SLOPES. EROSION PROTECTION BELOW FILL SLOPES SHALL BE PLACED IMMEDIATELY AFTER CLEARING, PRIOR TO EMBANKMENT CONSTRUCTION.
- ALL DISTURBED AREAS SHALL BE REVEGETATED AS QUICKLY AS POSSIBLE. ALL CUT AND FILL SLOPES SHALL BE SEEDED WITHIN 72 HOURS AFTER GRADING.
- 11. ALL WORK AREAS TO BE STABILIZED AT THE END OF EACH WORK DAY AND PRIOR TO ANY PREDICTED SIGNIFICANT RAIN EVENT.
- 12. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:
 A. BASE COURSE GRAVELS ARE INSTALLED IN AREAS TO BE PAYED
 B. A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED
 C. A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIP RAP HAS BEEN INSTALLED
 D. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED

- ALL CATCH BASINS, MANHOLES, AND DRAIN LINES SHALL BE THOROUGHLY CLEANED OF ALL SEDIMENT AND DEBRIS AFTER ALL AREAS HAVE BEEN STABILIZED.
- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SLOPE STABILITY DURING CONSTRUCTION.

APPROVED BY THE CITY OF ROCHESTER PLANNING BOARD

BOARD MEMBER BOARD MEMBER

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

EROSION CONTROL PLAN

PROPOSED AUTO DEALERSHIP 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

SCALE:1" . 40'(22X34)

JULY 9, 2019



REV. DATE

DESCRIPTION



Structural Engineers Traffic Engineers Land Surveyors

Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

DR RCK FB

CK HEG CADFILE 47159-01_Erosion.dwg 47159.01

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 266,454 SQUARE FEET (6.12 ACRES).

CRITICAL NOTE: THIS DRAWING IS PROVIDED FOR GENERAL GUIDANCE. ALL SPECIAL EROSION CONTROL MEASURES MUST BE EXECUTED IN ACCORDANCE WITH CURRENT STATE AND LOCAL REGULATIONS, APPROVED SWPPP AND PERMIT REQUIREMENT.

SEQUENCE OF MAJOR ACTIVITIES

- INSTALL STABILIZED CONSTRUCTION ENTRANCE AND TEMPORARY EROSION CONTROL MEASURES PER APPROVED SWPPP IF REGULIEFD

- SWPPP IF REQUIRED.

 DEMOLISH EXISTING SITE WORK DESIGNATED FOR REMOVAL.

 COMPLETE MAJOR GRADING OF SITE.

 COMPLETE MAJOR GRADING OF SITE.

 CONSTRUCT BUILDING PAD, STORMWATER SYSTEM, AND SITE UTILITIES.

 CONSTRUCT PARKING LOT.

 WHEN ALL CONSTRUCTION ACTIVITY IS COMPLETE AND SITE IS STABILIZED, REMOVE ALL INLET PROTECTION, SILT BARRIERS AND SEIDENT THAT HAS BEEN TRAPPED BY THESE DEVICES.

 CONSULT APPROVED SWPPP FOR CONDITIONS RELATED TO NOTICE OF TERMINATION, IF REQUIRED.

EROSION AND SEDIMENT CONTROLS AND STABILIZATION PRACTICES

STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES AND DISTURBED AREAS WHERE CONSTRUCTION ACTIVITY WILL NOT OCCUR FOR MORE THAN TWENTY ONE (21) CALENDAR DAYS BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR TEMPORARILY CEASED IN THAT AREA. ALL DISTURBED AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:

- BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED; A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED;
- A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED; OR EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.

DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STABILIZED CHANNELS WHERE POSSIBLE SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILT BARRIERS, ALL STORM DRAIN INLETS SHALL BE PROVIDED WITH BARRIER FILTERS. STONE RIPRAP SHALL BE PROVIDED AT THE OUTLETS OF DRAINAGE PIPES WHERE EROSIVE VELOCITIES ARE ENCOUNTERED.

STABILIZED CONSTRUCTION ENTRANCES SHALL BE INSTALLED.

INSTALLATION, MAINTENANCE AND INSPECTION OF EROSION AND SEDIMENT CONTROLS

THESE ARE THE GENERAL INSPECTION AND MAINTENANCE PRACTICES THAT WILL BE USED TO IMPLEMENT THE PLAN.

- 1. STABILIZATION OF ALL SWALES, DITCHES AND PONDS IS REQUIRED PRIOR TO DIRECTING FLOW TO THEM.

- 4. ALL MEASURES WILL BE MAINTAINED IN GOOD WORKING ORDER. IF A REPAIR IS NECESSARY, IT WILL BE INITIATED WITHIN 24 HOURS OF REPORT.
- 5. BUILT UP SEDIMENT WILL BE REMOVED FROM SILT BARRIER WHEN IT HAS REACHED ONE THIRD THE HEIGHT OF THE BARRIER.
- 6. ALL DIVERSION DIKES WILL BE INSPECTED AND ANY BREACHES PROMPTLY REPAIRED.
- 7. TEMPORARY SEEDING AND PLANTING WILL BE INSPECTED FOR BARE SPOTS, WASHOUTS, AND UNHEALTHY GROWTH.
- 8. A MAINTENANCE INSPECTION REPORT WILL BE MADE AFTER EACH INSPECTION
- THE CONTRACTOR'S SITE SUPERINTENDENT WILL BE RESPONSIBLE FOR INSPECTIONS, MAINTENANCE AND REPAIR
 ACTIVITIES, AND FILLING OUT THE INSPECTION AND MAINTENANCE REPORT.

FILTERS / BARRIERS

HYSICAL PROPERTY	TEST	REQUIREMEN
Н	TMFCC 04 11-A	5.0 TO 8.0

PARTICLE SIZE

TMECC 02.02-B 2" SIEVE AND MIN. 60% GREATER THAN THE 3/8" SIEVE

MATERIAL SHALL BE RELATIVELY FREE OF INERT OR FOREIGN MAN-MADE MATERIALS

MATERIAL SHALL BE WEED FREE AND DERIVED FROM A WELL-DECOMPOSED SOURCE OF ORGANIC MATTER, FREE FROM ANY REFUSE, CONTAMINANTS OR OTHER MATERIALS TOXIC TO PLANT GROWTH.

- C. SILT BARRIER SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFUL PURPOSE, BUT NOT BEFORE THE UPSLOPE AREAS HAS BEEN PERMANENTLY STABILIZED.

SEDIMENT BARRIERS SHALL BE INSTALLED PRIOR TO ANY SOIL DISTURBANCE OF THE CONTRIBUTING DRAINAGE AREA ABOVE THEM.

- A. SILT BARRIERS SHALL BE INSPECTED WEEKLY AND IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. THEY SHALL BE REPAIRED IF THERE ARE ANY SIGNS OF EROSION OR SEDMENTATION BELOW THEM. ANY REQUIRED REPAIRS SHALL BE MADE IMMEDIATELY. IF THERE ARE SIGNS OF UNDERCUTTING AT THE CENTER OR THE EDGES, OR IMPOUNDING OF LARGE VOLUMES OF WATER BEHIND THEM, SEDMENT BARRIERS SHALL BE REPLACED WITH A TEMPORARY CHECK DAM.
- B. SHOULD THE FABRIC DECOMPOSE OR BECOME INEFFECTIVE PRIOR TO THE END OF THE EXPECTED USABLE LIFE AND THE BARRIER STILL IS NECESSARY, THE FABRIC SHALL BE REPLACED PROMPTLY.
- C. SEDIMENT DEPOSITS SHOULD BE REMOVED AFTER EACH STORM EVENT. THEY MUST BE REMOVED WHEN DEPOSITS REACH APPROXIMATELY ONE THIRD (1/3) THE HEIGHT OF THE BARRIER.
- D. ANY SEDIMENT DEPOSITS REMAINING IN PLACE AFTER THE SILT BARRIER IS NO LONGER REQUIRED SHALL BE DRESSED TO CONFIRM WITH THE EXISTING GRADE, PREPARED AND SEEDED.



IN ORDER FOR MULCH TO BE EFFECTIVE, IT MUST BE IN PLACE PRIOR TO MAJOR STORM EVENTS. THERE ARE TWO (2) TYPES OF STANDARDS WHICH SHALL BE USED TO ASSURE THIS:

A. APPLY MULCH PRIOR TO ANY STORM EVENT.

THIS IS APPLICABLE WHEN WORKING WITHIN 100 FEET OF WETLANDS. IT WILL BE NECESSARY TO CLOSELY MONITOR WEATHER PREDICTIONS, USUALLY BY CONTACTING THE NATIONAL WEATHER SERVICE, TO HAVE ADEQUATE WARRING OF SIGNIFICANT STORMS.

THE TIME PERIOD CAN RANGE FROM 14 TO 21 DAYS OF INACTIVITY ON AN AREA, WHERE THE LENGTH OF TIME VARIES WITH SITE CONDITIONS. PROFESSIONAL JUDGMENT SHALL BE USED TO EVALUATE THE INTERACTION OF SITE CONDITIONS (SOIL ERODBIELITY, SEASON OF YEAR, EXTENT OF DISTURBANCE, PROXIMITY TO SENSITIVE RESOURCES, ETC.) AND THE POTENTIAL IMPACT OF EROSION ON ADJACENT AREAS TO CHOOSE AN APPROPRIATE TIME RESTRICTION.

WHEN MULCH IS APPLIED TO PROVIDE PROTECTION OVER WINTER (PAST THE GROWING SEASON) IT SHALL BE AT A RATE OF 6,000 POUNDS OF HAY OR STRAW PER ACRE. A TACKIFIER MAY BE ADDED TO THE MULCH.

ALL MULCHES MUST BE INSPECTED PERIODICALLY, IN PARTICULAR AFTER RAINSTORMS, TO CHECK FOR RILL EROSION. IF LESS THAN 90% OF THE SOIL SURFACE IS COVERED BY MULCH, ADDITIONAL MULCH SHALL BE IMMEDIATELY APPLIED.

D. VEGETATIVE PRACTICE

- AFTER ROUGH GRADING OF THE SUBGRADE HAS BEEN COMPLETED AND APPROVED, THE SUB GRADE SURFACE SHALL BE SCARRIED TO A DEPTH OF FOUR INCHES. THEN, FURNISH AND INSTALL A LAYER OF LOAM PROVIDING A ROLLED THICKNESS AS SPECIFIED IN THESE PLANS. ANY DEPRESSIONS WHICH MAY OCCUR MORE ROULING ROLLING LEFT CHARLES FILLED WITH ADDITIONAL LOAM, REGRADED AND REFOLLED UNTIL THE SURFACE IS TRUE TO THE PINNSHED LUNES AND OFFICES ALL COAM NECESSARY TO COMPLETE THE WORK UNDER THIS SECTION SHALL BE
- THE LOAM SHALL BE PREPARED TO RECEIVE SEED BY REMOVING STONES, FOREIGN OBJECTS AND GRADING TO ELIMINATE WATER POCKETS AND IRREGULARITIES PRIOR TO PLACING SEED, FINISH GRADING SHALL RESULT IN STRAIGHT UNIFORM GRADES AND SMOOTH, EVEN SUFFACES WITHOUT IRREGULARITIES TO LOW POINTS.
- 4. SHAPE THE AREAS TO THE LINES AND GRADES REQUIRED. THE SITE SUBCONTRACTOR'S ATTENTION IS DIRECTED TO THE SCHEDULING OF LOAMING AND SEEDING OF GRADED AREAS TO PERMIT SUFFICIENT TIME FOR THE STABILIZATION OF THESE AREAS. IT SHALL BE THE SITE SUBCONTRACTOR'S RESPONSIBILITY TO MAINTAIN THE AREAS DURING THE CONSTRUCTION PERIOD AND REGRADE, LOAM AND RESEED ANY DAMAGED AREAS.
- 5. ALL AREAS DISTURBED BY CONSTRUCTION WITHIN THE PROPERTY LINES AND NOT COVERED BY STRUCTURES, PAVEMENT, OR MULCH SHALL BE LOAMED AND SEEDED.
- LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF 2 TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5.
- 8. SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN. AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE ROUTED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4 1/2 POUNDS AND 5 1/2 POUNDS PER INCH OF WIDTH.
- 9. SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN, IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 109 DOUNDS PER LINEAU.
- 11. THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNIT THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED, AND ALL NOXIOUS WEEDS REMOVED.
- 13. UNLESS OTHERWISE APPROVED, SEEDING SHALL BE DONE DURING THE APPROXIMATE PERIODS OF EARLY SPRING TO SEPTEMBER 30, WHEN SOIL CONDITIONS AND WEATHER ARE SUITABLE FOR SUCH WORK, IN NO CASE SHALL THE WEED CONTENT EXCEED 1 PECENT BY WEIGHT. ALL SEED SHALL COMPLY WITH STATE DATE FEDERAL SEED LAWS. FOR TEMPORARY PLANTINGS AFTER SEPTEMBER 30, TO EARLY SPRING AND FOR TEMPORARY PROTECTION OF DISTURBED AREAS.
- A. FOLLOW ABOVE SLOPE, LOAM DEPTH AND GRADING REQUIREMENTS.
 B. FERTILIZER SHALL BE SPREAD AND WORKED INTO THE SURFACE AT A RATE OF 300 POUNDS PER ACRE.

MULCHING AND SEEDING SHALL BE APPLIED AT THE FOLLOWING RATES: WINTER RYE (FALL SEEDING) 2.5 LBS/1,000 SF OATS (SPRING SEEDING) 2.0 LBS/1,000 SF MULCH 1.5 TONS/ACRE

FLEXSTORM CATCH-IT FILTERS

ALL PRODUCTS MANUFACTURED BY INLET & PIPE PROTECTION, INC.
A DIVISION OF ADS, INC.
WWW.INLETFILTERS.COM

INLET PROTECTION

E. CATCH BASIN INLET PROTECTION

1. INLET BASKET STRUCTURE

- A. INLET PROTECTION SHALL BE INSTALLED IMMEDIATELY PRIOR TO DISTURBING PAVEMENT AND SHALL REMAIN IN PLACE AND MAINTAINED UNTIL PAVEMENT BINDER COURSE IS COMPLETE.
- B. MOLD 6X6, 42 LB. WIRE SUPPORT AROUND INLET FRAME AND GRATE AND EXTEND 6" BEYOND SIDES. SECURE FILTER FABRIC TO WIRE SUPPORT.
- C. THE FILTER FABRIC SHALL BE A GEOTEXTILE FABRIC; POLYESTER, POLYPROPYLENE, STABILIZED NYLON, POLYETHYLENE OR POLYVINYLIDENE CHLORIDE MEETING THE FOLLOWING SPECIFICATIONS:
- GRAB STRENGTH: 45 LB. MINIMUM IN ANY PRINCIPAL DIRECTION (ASTM D1682) MULLEN BURST STRENGTH: MIN. 60PSI (ASTM D774)
- E. THE INLET PROTECTION SHALL BE INSPECTED WITHIN 24 HOURS AFTER EACH RAINFALL OR DAILY DURING EXTENDED PERIODS OF PRECIPITATION. REPAIRS SHALL BE MADE IMMEDIATELY, AS NECESSARY, TO PREVENT PARTICLES FROM REACHING THE DRAINAGE SYSTEM AND/OR CAUSING SURFACE FLOODING.
- F. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT, OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED.

F. WINTER CONSTRUCTION SEQUENCE

- ALL PROPOSED POST-DEVELOPMENT LANDSCAPED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLINE EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1 AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE PLACEMENT OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING
- ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.
- AFTER OCTOBER 15TH, ALL TRAVEL SURFACES SHALL BE PROTECTED WITH A MINIMUM OF 3-INCHES OF CRUSHED GRAVEL PER NHOOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOWFALL AFTER EACH STORM EVENT.

AS INDICATED IN THE SEQUENCE OF MAJOR ACTIVITIES, SILT BARRIERS SHALL BE INSTALLED PRIOR TO COMMENCING ANY CLEARING OR GRADING OF THE SITE. STRUCTURAL CONTROLS SHALL BE INSTALLED CONCURRENTLY WITH THE APPLICABLE ACTIVITY. AREAS WHERE CONSTRUCTION ACTIVITY TEMPORARILY CEASES FOR MORE THAN TWENTY ONE (21) DAYS MIL BE STABILIZED WITH A TEMPORARY SEED AND MULCH WITHIN FOURTEEN (14) DAYS OF THE LAST DISTURBANCE. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN AN AREA, SILT BARRIERS AND ANY EARTH/DIKES WILL BE REMOVED ONCE PERMANENT MEASURES ARE ESTABLISHED.

- HAZARDOUS WASTE MATERIALS WILL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER. SITE PERSONNEL WILL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTERDENT.
- . SANITARY WASTE ALL SANITARY WASTE WILL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

MATERIAL MANAGEMENT PRACTICES
THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT WILL BE USED TO REDUCE THE RISK OF
SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING CONSTRUCTION TO
STORNWAITER RUNOFF:

GOOD HOUSEKEEPING:
THE FOLLOWING GOOD HOUSEKEEPING PRACTICES WILL BE FOLLOWED ON SITE DURING THE CONSTRUCTION PROJECT:

- A. AN EFFORT WILL BE MADE TO STORE ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB.
- (ORIGINAL IF POSSIBLE) CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE
- C. MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL WILL BE FOLLOWED
- D. THE SITE SUPERINTENDENT WILL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS. E. SUBSTANCES WILL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER.
- HAZARDOUS PRODUCTS:
 THE FOLLOWING PRACTICES WILL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
- A. PRODUCTS WILL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT RESEALABLE B. ORIGINAL LABELS AND MATERIAL SAFETY DATA WILL BE RETAINED FOR IMPORTANT PRODUCT INFORMATION.
- C. SURPLUS PRODUCT THAT MUST BE DISPOSED OF WILL BE DISCARDED ACCORDING TO THE MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL.

2. PRODUCT SPECIFICATION PRACTICES THE FOLLOWING PRODUCT SPECIFIC PRACTICES WILL BE FOLLOWED ON SITE:

PETROLEUM PRODUCTS:
ALL ON SITE VEHICLES WILL BE MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO REDUCE LEAKAGE. PETROLEUM PRODUCTS WILL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE WILL BE APPLIED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.

FERTILIZERS. FERTILIZERS USED WILL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS. DNCE APPLIED FERTILIZER WILL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO STORMWATER. STORAGE WILL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER WILL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.

CONCRETE TRUCKS WILL DISCHARGE AND WASH OUT SURPLUS CONCRETE OR DRUM WASH WATER IN A CONTAINED AREA DESIGNATED ON SITE.

HANNAH E. GIOVANNUCC No.15699

(ICENSED)




SPILL CONTROL PRACTICES

IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION THE FOLLOWING PRACTICES WILL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP:

- A. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP WILL BE CLEARLY POSTED AND SITE PERSONNEL WILL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES.
- B. MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP WILL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS WILL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS. RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE.
- D. THE SPILL AREA WILL BE KEPT WELL VENTILATED AND PERSONNEL WILL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A HAZARDOUS SUBSTANCE.
- E. SPILLS OF TOXIC OR HAZARDOUS MATERIAL WILL BE REPORTED TO THE APPROPRIATE STATE OR LOCAL GOVERNMENT AGENCY, REGARDLESS OF THE SIZE.
- F. THE SPILL PREVENTION PLAN WILL BE ADJUSTED TO INCLUDE MEASURES TO PREVENT THIS TYPE OF SPILL FROM RECURRING AND HOW TO CLEANUP THE SPILL IF IT RECURS. A DESCRIPTION OF THE SPILL, ITS CAUSE, AND THE CLEANUP MEASURES WILL BE INCLUDED.
- G. THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS WILL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.

DUST CONTROL

THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST THROUGHOUT THE CONSTRUCTION PERIOD. DUST CONTROL METHODS SHALL INCLUDE, BUT NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY MULCHING. DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ABUTTING AREAS.



- 1. FILTER CLOTH WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE SURFACE.
- 3. MAINTENANCE THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS—OF—WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS—OF—WAY MUST BE REMOVED IMMEDIATELY.

5. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN STORM EVENT. STABILIZED CONSTRUCTION ENTRANCE

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

EROSION CONTROL NOTES

PROPOSED AUTO DEALERSHIP 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019



Structural Engineers Traffic Engineers Land Surveyors

Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

47159.01 CK HEG CADFILE 47159-01_Details.dwg


Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110


ill rights reserved. These plans and materials may not be copied, uplicated, replicated or otherwise reproduced in any form whatsoever ithout the prior written permission of Thomas F. Moran, Inc. not effective unless signed by a duly authorized officer of

NOTES:

INSTALL PER MANUFACTURER'S SPECIFICATIONS.
INSPECTION SHOULD OCCUR FOLLOWING ANY RAIN EVENT >}".
EMPTY THE SEDIMENT BAG PER MANUFACTURER'S SPECIFICATIONS.
REMOVED CAKED ON SILT FROM SEDIMENT BAG AND FLUSH WITH
MEDIUM SPRAY WITH OPTIMAL FILTRATION.

REPLACE BAG IF TORN OR PUNCTURED TO >2" DIAMETER ON LOWER HALF OF BAG.





- TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M24B TYPE "F". APPLY TWO COATS.
- 2. SYMBOLS & PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT, LATEST EDITION.
- 3. 2% MAXIMUM CROSS SLOPE ALLOWED IN ACCESSIBLE PARKING SPACES AND ACCESS AISLES.

TYPICAL PARKING LAYOUT

- BLUE BACKGROUND

LIGHT POLE BASE (24" MOUNTING HEIGHT)

NOTES:
1. CONCRETE TO BE 4000 PSI.

BASE SHALL BE USED FOR ALL POLES WITH FIXTURE MOUNTING HEIGHT LESS THAN 16-FEET.

BOND GROUND ROD TO LIGHT STANDARD

0400

RIGID STEEL

FOUR 3/4" ANCHOR BOLTS WITH 4"
HOOK, BURR THREADS AFTER SETTING
POLE. BOLT TEMPLATE TO PROVIDE FOR
POLES IDENTIFIED TO BE RELOCATED
GROUT AFTER POLE IS SET AND


- RIGID STEEL ELBOW (SEE SITE PLAN FOR SIZE)

-3/4" Ø MIN. COPPER CLAD STEE GROUND ROD MIN. 2'-0" BELOW BOTTOM OF PIER

#3 TIES AT 12" ON CENTER

- SCHEDULE 40 PVC

PLAN VIEW



HEX NUTS (4 REQ'D.)

HEX NUTS (4 REQ'D.)-

3/4"ø GROUND ROD -

PLAIN WASHERS (4 REQ'D.)

FINISH GRADES PLAIN WASHERS (4 REQ'D.) —

- MORTAR JOINTS AND OTHER INSTALLATION TO BE AS SPECIFIED IN NHOOT SECTION 609.
- ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.

VERTICAL GRANITE CURB

3,000 PSI, 7% AIR ENTRAINED CONCRETE WITH #5 REBAR © 12" O.C. EACH WAY TOP. THICKEN SLAB TO 12" ALONG OUTSIDE PERIMETER LIGHT BROOM 1% SLOPE TO FRONT - SLOPE= 1:1 -8" GRAVEL BASE (NHDOT 304.3) SECTION VIEW

NOTES

1. PROVIDE CLEAN BUTT TO EXISTING PAVEMENT - USE TACK COAT.

1/8"x1" DEEP HAND TOOLED JOINT

1" RIGID STEEL TO POLE


CONCRETE PAD

CONTROL JOINT

- TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F". APPLY TWO COATS.
- SYMBOLS AND PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT, LATEST EDITION.

ACCESSIBLE GRAPHIC SYMBOL

- WHITE BORDER




1. HYDRANT INSTALLATION AND OPERATION, MANUFACTURER AND MODEL, AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE IN ACCORDANCE WITH VILLAGE OF DOBBS TERRY AND FIRE DEPARTMENT ESTABLISHED RULES AND PROCEDURES.

FIRE HYDRANT

2. HYDRANT SHALL BE PAINTED RED.





NOTES

- BASE PLATE

RIGID STEEL
CONDUIT - SEE
SITE LIGHTING PLAN
FOR LOCATIONS &
NUMBER REQUIRED

BOLT VIEW

NOTES:


1. ALL MATERIAL TO MEET FILTREXX^MSPECIFICATIONS

2. FILTERSOXX COMPOST/SOIL/ROCK/SEED FILL TO MEET APPLICATION


3. COMPOST MATERIAL TO BE DISPERSED ON SITE, AS DETERMINED BY ENGINEER.

FILTREXX[™] FILTERSOXX[™] STAKING


NOT TO SCALE



CAST-IN-PLACE CONCRETE CURB




STOP BAR & LEGEND



BOLLARD SHALL BE PAINTED WITH PRIMER & 2 COATS OF SAFETY YELLOW PAINT.

BOLLARD





LENGTH: AS REQUIRED

WEIGHT PER LINEAR FOOT: 2.50 LBS (MIN) HOLES: 3/8" DIAMETER, 1" C-C FULL LENGTH

STEEL: SHALL CONFORM TO ASTM A-499 (GRADE 60) OR
ASTM A-576 (GRADE 1070 - 1080)

EINISH: SHALL BE PAINTED WITH 2 COATS OF AN APPROVED
MEDIUM GREEN BAKED-ON OR AIR-DRIED PAINT OF
WEATHER RESISTANT QUALITY, ALL FABRICATION SHALL
BE COMPLETE BEFORE PAINTING.

 ${\color{red} {\rm NOTE:}}$ 1. Where ledge application exists, drill & grout to a

- WHERE LEDGE APPLICATION EXISTS, DMILL & GMOUT TO A MINIMUM OF 2'.
 ALL SIGNAGE SHALL FOLLOW THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES STANDARDS AND NHDOT STANDARDS.
 SIGN, HARDWARE, AND INSTALLATION SHALL CONFORM TO THE LATEST NHDOT STANDARD SPECIFICATIONS.

SIGN POST

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2


DETAILS

PROPOSED AUTO DEALERSHIP **400 NORTH MAIN STREET** ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019





Land Surveyors MSC

Portsmouth, NH 03801 Phone (603) 431-2222 Fox (603) 431-0910

DR RCK FB
CK HEG CADFILE 47159-01_Details.dwg

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

Il rights reserved. These plans and materials may not be copied, olicated, replicated or otherwise reproduced in any form whatsoeve mout the prior written permission of Thomas F. Moran, Inc. This plan is not effective unless signed by a duly authorized officer

DIG SAFE CONTACT DIG SAFE 72 BUSINESS HOURS PRIOR TO CONSTRUCTION PER FIRE AND WATER DEPARTMENT.

- 2. INSTALL DARK BROWN VINYL PRIVACY SLATS IN FENCE & GATES WHERE INDICATED.
- 3. PROVIDE CHAIN LINK GATE TO ACCESS DUMPSTER.

CHAIN LINK FENCE


NOTE

NOTES:

- 1. 2" MESH FABRIC, 9 GAUGE WIRE FOR FENCE. LINE POSTS ARE TO BE A 2 1/2" DIAMETER 16 GAUGE. TOP RAIL SHOULD BE 1 1/2" DIAMETER 16 GAUGE. ALL PER ASTM SPECIFICATIONS.

Civil Engineers Structural Engineers Traffic Engineers

C-14



STANDARD DUTY PAVEMENT

HEAVY DUTY PAVEMENT

NOTES


- 1. SEE GRADING & EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.
- PROVIDE CLEAN BUTT TO EXISTING PAVEMENT— USE TACK COAT. A TACK COAT SHALL ALSO BE PLACED BETWEEN GRAVEL
 COURSE AND SUCCESSIVE LAYERS OF BITUMINOUS CONCRETE. SPECIFICALLY, A TACK COAT SHALL BE PLACED ATOP THE BINDER
 COURSE PAVEMENT PRIOR TO PLACING THE WEARING COURSE.
- 3. REMOVE ALL LOAM AND/OR YIELDING MATERIAL BELOW PAVEMENT.
- 4. BITUMINOUS MATERIALS SHALL CONFORM TO NHDOT SPECIFICATION SECTION 401.
- 5. BITUMINOUS CONCRETE SHALL BE COMPACTED TO AT LEAST 92-97% OF THEORETICAL MAXIMUM DENSITY AS DETERMINED BY ASTM D2041, PLACEMENT TEMPERATURES OF BITUMINOUS CONCRETE MIXES, IN GENERAL, RANGE BETWEEN 270 AND 310 DEGREES FAHRENHEIT.
- 6. PAVEMENT BASE COURSE AGGREGATE SHALL CONFORM TO NHDOT SPECIFICATION SECTION 304, ITEM 304.3 AND COMPACTED TO A MINIMUM OF 95% OF ASTM D-1557.
- 7. PAVEMENT SUBBASE COURSE AGGREGATE AND AGGREGATE FOR SUBGRADE REPAIR AREAS SHALL BE SUITABLE FOR USE AS STRUCTURAL FILL AND BE PROOF ROLLED AND COMPACTED TO 95% OF ASTM D-1557.
- 8. THE EXPOSED SOIL SUBGRADE SHOULD BE PROOF ROLLED PRIOR TO THE PLACEMENT OF SUBBASE GRAVEL, AND SOFT AREAS SHOULD BE REPAIRED AND REPLACED.
- 9. LOCATION OF HEAVY DUTY PAVEMENT SHALL BE AS SHOWN ON THE LAYOUT PLAN. ALL OTHER LOCATIONS SHALL BE STANDARD DUTY PAVEMENT.
- 10. EXACT AREAS TO RECEIVE FULL-DEPTH PAVEMENT SECTION BASE AND SUB-BASE SHALL BE DETERMINED IN FIELD AT THE TIME OF CONSTRUCTION.

PAVEMENT SECTION

(NHDOT ITEM 609.2X) SLOPE VARIES CRUSHED GRAVE PAVEMENT SECTION (SEE DETAIL) (NHDOT ITEM 304.3 FINISHED GRADE NOTES

MORTAR JOINTS AND OTHER INSTALLATION TO BE AS SPECIFIED IN NHOOT SECTION 609.
 ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.

SLOPED GRANITE CURB NOT TO SCALE



UTILITY TRENCH


SECTION

PLAN

RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICAN WITH DISABILITIES ACT, LATEST EDITION.

SIDEWALK TIP DOWN RAMP (TYPE C)

1: 12 MAX.




NOTES

- 1. MANHOLE FRAME & COVER: SHALL BE PAMREX CLASS D400, HINGED, OR APPROVED EQUAL BY THE CITY ENGINEER.
 2. MANHOLE TO BE STAMPED TO SAY "STORM".
 3. COVERS AND FRAMES TO BE COATED BLACK.
 4. MANHOLES SHALL MEET NHDOT SPECIFICATIONS.
 5. ALL COMPONENTS SHALL BE DESIGNED FOR HS-20 LOADING.
 6. REINFORCING SHALL CONFORM TO ASTM 185 OR ASTM 1497 & ASTM A615, GRADE 60.
 7. ALL CONCRETE SHALL BE NHDOT CLASS A.
 8. LARGER DIAMETER STRUCTURES SHALL BE USED AS REQUIRED DUE TO NUMBER, ANGLE OR SIZE OF PIPES AT THE STRUCTURE.

DRAIN MANHOLE


NOT TO SCALE



1. USE KEY JOINT AT ALL LOCATIONS WHERE OVERLAY MEETS EXISTING PAVEMENT.

2. NEW PAVEMENT SHALL BE FLUSH WITH EXISITING PAVEMENT AND SHALL MEET OVERLAY GRADE WHERE IT ABUTS EXISTING PAVEMENT TO BE OVERLAYED.


KEY JOINT DETAIL



1. ALL SECTIONS SHALL BE PRECAST CONCRETE NHDOT CLASS AA, 4,000 PSI. 2. CATCH BASINS SHALL MEET NHDOT SPECIFICATIONS. 3. ALL COMPONENTS SHALL BE DESIGNED FOR HS –20 LOADING. 4. LARGER DIAMETER STRUCTURES SHALL BE USED AS REQUIRED DUE TO NUMBER, ANGLE OR SIZE OF PIPES AT THE STRUCTURE.

ECCENTRIC CATCH BASIN WITH SNOUT


DIG SAFE



CONCRETE SIDEWALK

SECTION DETECTABLE WARNING STRIP (FULL WIDTH) - SCORE LINES UP-RAMP 0 1: 12 SLOPE MAX. PLAN RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICAN WITH DISABILITIES ACT, LATEST EDITION.

STANDARD ACCESSIBLE RAMP (TYPE A)



SIDEWALK TIP DOWN RAMP (TYPE B)

8/13/2019 1 8/13/19 TRG COMMENTS
REV. DATE DKE HEG DR CK DESCRIPTION

SITE DEVELOPMENT PLANS

TAX MAP 114 LOT 2

DETAILS

PROPOSED AUTO DEALERSHIP 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019



47159.01

Structural Engineers Traffic Engineers Land Surveyors MSC

Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

CK HEG CADFILE 47159-01_Detoils.dwg C-15

Il rights reserved. These plans and materials may not be copied. uplicated, replicated or otherwise reproduced in any form whatsoever ithout the prior written permission of Thomas F. Moran, Inc. his plan is not effective unless signed by a duly authorized officer homas F. Moran, Inc.


Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110



PLEASE NOTE:

1. THE LISTED ASSITIO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".


2. AS AN ALTERNATE TO PROCTOR TESTING AND FIELD DENSITY MEASUREMENTS ON OPEN GRADED STONE, STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 9"[229 mm] (MAX) LIFTS USING TWO FULL COVERAGES WITH AN APPROPRIATE COMPACTOR.



NOTES

1. THE DESIGN INFILTRATION RATE FOR THE PROPOSED FILL BENEATH THE SYSTEM IS 5 INCHES PER HOUR AND SHALL BE NO GREATER
THAN 10 INCHES PER HOUR, AS DETERMINED BY LABORATORY METHODS DESCRIBED IN ENV-WO 1504.14(e).
2. THE INSTALLED CHAMBER SYSTEM SHALL PROVIDE THE LOAD FACTORS SPECIFIED IN THE ASHTO LAFD BRIDGE DESIGN SPECIFICATIONS
SECTION 12.12 FOR EARTH AND LIVE LOADS WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCE.

STORMTECH SC-740 UNDERGROUND INFILTRATION BASIN



NOTES
1. THE DESIGN INFILTRATION RATE FOR THE PROPOSED FILL BENEATH THE SYSTEM IS 5 INCHES PER HOUR AND SHALL BE NO GREATER
THAN 10 INCHES PER HOUR, AS DETERMINED BY LABORATORY METHODS DESCRIBED IN ENV-WO 1504,14(e).
2. THE INSTALLED CHAMBER'S SYSTEM SHALL PROVIDE THE LOAD FACTORS SPECIFICD IN THE ASHTOL LIFE BRIDED ESIGN SPECIFICATIONS
SECTION 12.12 FOR EARTH AND LIVE LOADS WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCE.

STORMTECH SC-310 UNDERGROUND INFILTRATION BASIN



- 24" FILL SOIL 2 LAYERS OF ADS 315ST WOVEN GEOTEXTILE (OR EQUAL) BETWEEN FOUNDATION STONE AND CHAMBERS SC-740: 5'-6" WIDE STRIP SC-310: 4'-0" WIDE STRIP

THE DESIGN INFILTRATION RATE FOR THE PROPOSED FILL BENEATH THE SYSTEM IS 5 INCHES PER HOUR AND SHALL BE NO GREATER THAN 10 INCHES PER HOUR, AS DETERMINED BY LABORATORY METHODS DESCRIBED IN EVW-WO 1504.14(e).

STORMTECH SC-740 LENGTH

BOTTOM OF CHAMBER

STORMTECH SC-310 LENGTH

TOP OF STONE

B BOTTOM OF STONE

MIN. PAVEMENT ELEVATION 232.25

145.6 110.42

224.50 224.50

145.60 74.83


228.63

226.30

ISOLATOR ROW PROFILE

TYPICAL SECTION

-12" COMPACTED 3/8" CRUSHED STONE



SEWER MANHOLE

TAX MAP 114 LOT 2 **DETAILS**

PIPE

CONCRETE -

SECTION A-A

(CENSED

PROPOSED AUTO DEALERSHIP 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE

SITE DEVELOPMENT PLANS

OWNED BY & PREPARED FOR

400 NORTH MAIN STREET, LLC

JULY 9, 2019





Structural Engineers Traffic Engineers Land Surveyors MSC

Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

3'-0"-

SECTION A-A VIEW

3'-0"-

SECTION B-B VIEW

BAFFLE WALL DETAIL


 DR
 RCK
 FB


 CK
 HEG
 CADFILE
 47159-D1_Details.dwg
 47159.01


All rights reserved. These plans and materials may not be copied,


his plan is not effective unless signed by a duly authorized officer


Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110











SCALE: 1 INCH = 40 FT

NOTES:

1. REFERENCE: TAX MAP 114, LOT 002

2. TOTAL PARCEL AREA: 10.99 AC.

WETLAND BUFFER

3. OWNER OF RECORD: 400 NORTH MAIN STREET, LLC 549 ROUTE 1 BYPASS PORTSMOUTH, NH 03801 S.C.R.D. BK 4081, PG 957

ZONE: HIGHWAY COMMERCIAL DIMENSIONAL REQUIREMENTS:

MIN. LOT AREA

20,000 sq.ft.

MIN. LOT AREA/DWELLING UNIT 5,000 sq.ft./7,500 sq.ft.

MIN. FRONTAGE
MIN. FRONTAGE
MIN. FRONT SETBACK
MIN. SIDE SETBACK
MIN. REAR SETBACK
MIN. REAR SETBACK
MAX. LOT COVERAGE
MAX. BUILDING STORIES

ZONING INFORMATION LISTED HEREON IS BASED ON THE CITY OF ROCHESTER ZONING ORDINANCE DATED 02/02/17 AS AVAILABLE ON THE CITY WEBSITE ON 01/08/18. ADDITIONAL REQULATIONS APPLY, AND REFERENCE IS HEREBY MADE TO THE EFFECTIVE ZONING ORDINANCE. THE LAND OWNER IS RESPONSIBLE FOR COMPLYING WITH ALL APPLICABLE MUNICIPAL, STATE AND FEDERAL REGULATIONS.

- FIELD SURVEY PERFORMED BY DOUCET SURVEY DURING DECEMBER 2017 & MARCH 2019 USING A TRIMBU 88 TOTAL STATION WITH A TRIMBLE TSC3 DATA COLLECTOR AND A SOKKIA B21 AUTO LEVEL TRAVERSE ADJUSTMENT BASED ON LEAST SOUARE ANALYSIS.
- ADDITIONAL FIELD SURVEY PERFORMED BY L.P.S. ON DECEMBER 10, 2017 USING A DJ PHANTOM PRO UAV WITH AN AVERAGE GROUND SAMPLING DISTANCE OF 1.04 CM/0.41 IN, DATA WAS PROCESSED USING PIX44 DSOFTWARE.
- JURISDICTIONAL WETLANDS DELINEATED BY GOVE ENVIRONMENTAL SERVICES, INC. ON SEPTEMBER 7, 2017
 IN ACCORDING TO THE CORPS OF ENGINEERS WETLAND DELINEATION MANUAL. AND THE REGIONAL
 SUPPLEMENT TO THE CORPS OF ENGINEERS WETLAND DELINEATION MANUAL. NORTHCENTRAL AND
 NORTHEAST REGION, VERSION 2.0, JANUARY 2012, US ARMY CORPS OF ENGINEERS.
- 8. FLOOD HAZARD ZONE: "X" & "AE", PER FIRM MAP 33017C0203D, DATED 5/17/05.
- HORIZONTAL DATUM BASED ON NEW HAMPSHIRE STATE PLANE(2800) NAD83(2011) DERIVED FROM REDUNDANT GPS OBSERVATIONS UTILIZING THE KEYNET GPS VRS NETWORK, CONSISTENT WITH CITY OF ROCHESTER GIS DATUM.
- 10. VERTICAL DATUM IS BASED ON NHDOT DISK H 52 1978 NAVD88 ELEVATION = 231.79'.
- 11. PROPER FIELD PROCEDURES WERE FOLLOWED IN ORDER TO GENERATE CONTOURS AT 1' INTERVALS. ANY MODIFICATION OF THIS INTERVAL WILL DIMINISH THE INTEGRITY OF THE DATA, AND DOUGET SURVEY, INC. WILL NOT BE RESPONSIBLE FOR ANY SUCH ALTERATION PERFORMED BY THE USER.
- 12. UNDERGROUND UTILITIES SHOWN HEREON ARE BASED ON OBSERVABLE PHYSICAL EVIDENCE AND PAINT MARKS FOUND ON-SITE.
- 13. THE ACCURACY OF MEASURED UTILITY INVERTS AND PIPE SIZES/TYPES IS SUBJECT TO NUMEROUS FIELD CONDITIONS, INCLUDING: THE ABILITY TO MAKE VISUAL OBSERVATIONS, DIRECT ACCESS TO THE VARIOUS ELEMENTS, MANHOLE CONFIGURATION, ETC.
- 14. THE INTENT OF THIS PLAN IS TO SHOW THE LOCATION OF BOUNDARIES IN ACCORDANCE WITH AND IN RELATION TO THE CURRENT LEGAL DESCRIPTION, AND IS NOT AN ATTEMPT TO DEFINE UNWRITTEN RIGHTS DETERMINE THE EXTENT OF OWNERSHIP, OR DEFINE THE LIMITS OF TITLE.
- 15. DUE TO THE COMPLEXITY OF RESEARCHING ROAD RECORDS AS A RESULT OF INCOMPLETE, UNORGANIZED, INCONCLUSING, OBLITERATED, OR LOST DOCUMENTS, THERE IS AN INHERENT UNCERTAINTY INVOLVED WHE ATTEMPTING TO DETERMINE THE LOCATION AND WIDTH OF A ROADWAY RIGHT OF WAY. THE EXTENT OF (THE ROAD(S)) AS DEPICTED HEREON ARE BASED ON RESEARCH CONDUCTED AT THE STRAFFORD COUNT REGISTRY OF DEEDS AND NH DEPARTMENT OF TRANSPORTATION.
- 16. ALL ELECTRIC, GAS, TEL. WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION, THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WHIT THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888—DIG-SAFE.

REFERENCE PLANS:

- "STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION, RIGHT-OF-WAY PLANS, NH PROJECT NO. 10620-D SPAULDING TURNPIKE NH ROUTE 16." DATED JANUARY 11, 2011.
- STATE OF NEW HAMPSHIRE DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS, PLANS OF PROPOSED LS 1827(I) NH NO. P-2692-V." DATED FEBRUARY 28, 1985.
- "ALTA/ACSM LAND TITLE SURVEY, TAX MAP 114 LOT 1, PROPERTY OF REL COMMONS, LLC, 306 NORTH MAIN STREET, ROCHESTER, NEW HAMPSHIRE, COUNTY OF STRAFFORD" DATED FEBRUARY 12, 2015 BY MSC NOT RECORDED.
- "PLAN OF LAND OF FIRST DEVELOPMENT CORPORATION GLOBE DEPARTMENT STORES ROUTE 11 ROCHESTER, NH" DATED NOV. 27, 1990 BY BERRY SURVEYING & ENGINEERING S.C.R.D. PLAN 38A-41.
- 5. 400 NORTH MAIN STREET DIGITAL CAD FILE FURNISHED BY NORWAY PLAINS ASSOCIATES.

EXISTING CONDITIONS PLAN FOR

MSC CIVIL ENGINEERS

OF

TAX MAP 114 LOT 2 400 NORTH MAIN STREET ROCHESTER, NEW HAMPSHIRE


_			
1	06/27/19	ADD PARCEL LABELS	M.T.L
NO.	DATE	DESCRIPTION	BY

PRAWN BY: M.T.L.	DATE: MARCH 26, 2019			
HECKED BY: J.F.K.	DRAWING NO.: 5228A			
OB NO.: 5228	SHEET OF 2			





Serving Your Professional Surveying & Mapping Needs 102 Kent Place, Newmarket, NH 03857 (603) 659-6560 2 Commerce Drive (Suite 202) Bedford, NH 03110 (603) 614-4060 10 Storer Street (Riverview Suite) Kennebunk, ME (207) 502-7005 http://www.doucetsurvey.com





Project Info: Rochester **Buick GMC**

400 North Main St Rochester NH

Sheet Status:

JOB NO: DRAFTED: CHECKED: 19010 MLN JMT

SCALE 3/32" = 1'-0"

First Floor Plan

PROJECT NORTH

1 FIRST FLOOR PLAN
3/32" = 1'-0"

First Floor S.F. = 20,785

Second Floor S.F. = 4,874

Total = 25,659



Project Info: Rochester **Buick GMC**

400 North Main St Rochester NH

Sheet Status:

JOB NO DRAFTED: CHECKED:

SCALE 3/32" = 1'-0"

Second Floor

Plan

SECOND FLOOR PLAN
3/32" = 1'-0"

First Floor S.F. = 20,785

Second Floor S.F. = 4,874

= 25,659

PROJECT NORTH



DESIGN | BUILD Architectural Document Set - *Prepared For Exclusive Use By* : WHITCHER BUILDERS

GENERAL ROOF PLAN NOTES;

I) ALL ROOF SLOPES ARE 1/A* PER FOOT MIN.
2) PITCH STELL AS REGO. TO ACHEVE ROOF SLOPES INDICATED ON DWGS.
3) HATCH INDICATES BITENT OF SLOPED ROOF INSULATION.
4) ALL RUBBER ROOFS TO BE GO MILE FULLY ADHERED E.P.D.M.
5) MIN. ROOF INSULATION THICKNESS SHALL BE 3' OF BRACE TOP OF ALL PARAPET WALLS WITH METAL STUD KICKER.
WALL SLOPED 10/12, REFER TO SECTIONS FOR MORE DETAILS.

TEXT LEGEND: R.D. = ROOF DRAIN C.R.D. = OVER FLOW ROOF DRAIN = INDICATES TAPERED INSULATION = STANDING SEAM MTL. ROOF @ P.E.B.

Project Info:
Rochester **Buick GMC**

400 North Main St Rochester NH


Planning Board Set N.F.C. JOB NO: DRAFTED: CHECKED: 19010 MLN JMT


SCALE 3/32" = 1'-0"

Sheet Title:

Roof Plan

PROJECT NORTH





- ELEVATION NOTES:

 1) REFER TO SHEET A3.3 FOR ALL ACM PANEL SIZES # JOINT LOCATIONS
 - REFER TO SHEET A3.3 FOR ALL CURTAIN WALL & STOREFRONT MULLION GRO DIMENSIONS

 REFER TO SHEET A6.1 FOR DOOR & WINDOW SCHEDULES & LEGENDS

- REFER TO FLOOR PLANS FOR ALL DITERIOR WALL TAGS
 REFER TO SHEET AA O. FOR ALL WALL THES
 ALL EXTERIOR FINISH MATERIALS 4 COLORS ARE PER GM DESIGN STANDARDS
 LIGHTING LAYOUT FOR DESIGN INTENT ONLY. ALL FIXTURE PLACEMENTS TO BE BY
- ELECTRICAL CONTRACTOR'S DESIGN / BUILD ENGINEER
- REFER TO TABLE C702.4 ON CODE REVIEW SHEET CR. I FOR ENVELOPE FENESTRATION WAXMUM ALLOWABLE U.F.ACTORS

 ALL ALPOLIC ACM PANELS TO BE DRY-JOINT SYSTEM

- EXTERIOR FINISH SCHEDULE

 1. ACM-1 = ALPOLIC TBL BLACK 3-4TBL-G75

 2. ACM-2 = ALPOLIC TILA BRUISHED HARLINE ALUMINUM

 3. ACM-3 = ALPOLIC RW WHITE WHITE


 4. MP-1 = ATAS (SOLEREN VL MCRO-BEAD BONE WHITE

- GL-I = SOLARBAND LOW E CLEAR ANODIZED ALUMINUM OR SILVER METALLIC FRAMES
- MP-1 = ATAS BELVEDERE DOVE GRAY MECH. SCREEN



DESIGN | BUILD Architectural Document Set - Prepared For Exclusive Use By:

WHITCHER BUILDERS



2 SOUTH EXTERIOR ELEVATION
1/8" = 1'-0"

(G.4) (D.8) (MJ) (MA) ROOF TOP HVAC UNIT METAL PANEL MECHANICAL SCREENS MP-1 ROOF ACCESS HATCH BEYOND RUN E.P.D.M. DOWN WALL & TERMINATE (TYP. @ ALL ROOF TOP MECH UNITS) @ STANDING SEAM MTL. ROOF " MTL. STUD KICKER WALL,W/ 3/4" T&G EXT. PARAPET KICKER WALL - ELEVATOR PENTHOUSE P.E.B. TRIM ALUM, TRIP CAP, PER MANUF ROOF SHEATHING EXTEND ROOF E.P.D.M. UP & ROOF BEYOND LAP OVER TOP OF WALL, TYP. E.P.D.M. ROOF MEMBRANE, RUN UP WALL & LAP OVER T.O. PARAPET RUN E.P.D.M. DOWN WALL & TERMINATE @ STANDING SEAM MTL. ROOF P.E.B. TRIM ALUM. TRIP CAP, PER MANUF. T.O. ROOF (HIGH PT.) STANDNING SEAM MTL. ROOF, 1.0.W. P.E.B. PER P.E.B. MANUF. COVERED NEW CAR DELIVER PLANNING BOARD SET OFFICED SCY MTL. WALL PANELS @ SHOP - IMP-I ACM MTI WALL PANE B (B) **B B** - WALL MOUNTED EXT. BEYOND - ACM-1 ROOF TOP HVAC UNIT FULL GLAZED OVERHEAD DOORS - STANDING SEAM MTL, ROOF SECOND FLOOR WALL MOUNTED EXT. - ELEC. CAR CHARGERS (128A) (28B) (230) (24B) FIRST FLOOR REINFORCED CONC. CONC. FILLED 8" Dia. PTD. STL. EXT. FLUSH MTL. DOORS, PTD. (TYP.) -MTL. WALL PANELS - IMP-1 OVERHEAD DOORS W/ V/S/ON LITES FOUNDATION WALL & FOOTINGS. BOLLARDS, TYP. @ ALL O.H. DOORS PER STR. DWG'S. 1 WEST EXTERIOR ELEVATION 1/8" = 1'-0"

Project Info: Rochester **Buick GMC**

400 North Main St Rochester NH

Sheet Status:


19010 MLN JMT

1/8" = 1'-0"

Sheet Title: Exterior Elevations

A3.2






Luminaire Schedule							
Symbol	Label	Qty	Description	LLF	Lum. Watts	Lum. Lumens	
-	SL1A	12	VMX-1-T4-80LC-3-4K-UNV	0.900	87	11593	
	SL1B	6	VMX-1-T4-80LC-3-4K-UNV	0.900	87	11593	
-	SL2	13	VMX-1-T4-80LC-3-4K-UNV_CLS-	0.900	88	7735	
-	SL3A	4	VMX-1-T5-80LC-3-4K-UNV	0.900	87	12442	
	SL3B	3	VMX-1-T5-80LC-3-4K-UNV	0.900	87	12442	
	WM1	9	VSC-1-T4-32LC-3-4K-UNV	0.900	37	4642	
\odot	RC1	6	Nora Lighting # NC2-631L1540FWSF	0.900	15.04	1132	


Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
Property Line	Illuminance	Fc	0.13	1.0	0.0	N.A.	N.A.
Site Points	Illuminance	Fc	0.84	6.8	0.0	N.A.	N.A.
Display Section 1	Illuminance	Fc	1.84	5.0	0.4	4.60	12.50
Display Section 2	Illuminance	Fc	2.08	4.7	0.8	2.60	5.88
Display Section 3	Illuminance	Fc	1.75	4.9	0.3	5.83	16.33
Display Section 4	Illuminance	Fc	1.49	3.7	0.3	4.97	12.33
Display Section 5	Illuminance	Fc	2.73	5.0	0.7	3.90	7.14


ABBREVIATIONS:

Avg= Average AFG= Above Finished Grade CF = Compact Fluorescent CV= Coefficient of variation CV= Coefficient of variation fc = Footcandles HPS = High Pressure Sodium LLF= Light Loss Factor MH = Mounting Height NTS = Not to Scale PSMH = Pulse Start Metal Halide SF = Square foot W = Watts

- A. CALCULATION POINTS INDICATED ARE BASED ON MAINTAINED FOOTCANDLE (FC) LEVELS AFTER A LIGHT LOSS FACTOR (LLF) IS APPLIED TO FIXTURE. REFER TO SCHEDULES FOR LLF AND LUMEN INFORMATION.
- B. REFER TO PLAN FOR FIXTURE MOUNTING HEIGHTS.
- C. CALCULATION POINTS TAKEN AT GRADE.







Experience the light $^{ extstyle{ iny M}}$

CircleT - 781-821-1700 02021 www.skandassociates.

20/22 Carver Canton, MA C

SSO

PROJECT NAME

400 North Main Street-Rochester, NH

CLIENT MSC

170 Commerce Way - Suite 102, Portsmouth, NH 03801

SEAL

REVISIONS No. Description 1. TRG Comments Issue Date: July 3, 2019

Project #: 19143 Drawn: AD Checked: TJ Approved: MC

Scale: 1"=40'-0" DRAWING NAME Lighting Plan,

Schedules and **Specifications**

DRAWING NUMBER

SL1

Copyright SK & Associates Inc. 2018